
Hisense | COMMERCIAL DISPLAY







Introducing the latest generation of Digital Signage Displays

Hisense Digital Signage is designed to serve multiple business applications: public spaces, transportation systems, museums, stadiums, retail stores, hotels, restaurants and corporate buildings. With the GM50D series, it delivers powerful engagement from any devices, boost business with real-time updates, data-driven insights and visually appealing content, manage and control devices at anytime from anywhere, and simplify the cable management by conecting a series of displays to a single video output.
























4K UHD

Delivers superior resolution that allows more details to be displayed on an image. The materials, the textures, the skin texture and the backgrounds: everything is richer and more realistic. 4K UHD provides four times the resolution of Full HD (1080p), with a resolution of 3840 x 2160 pixels. This higher pixel density results in sharper and more detailed images and videos, which can significantly enhance the viewing experience.

Anti Glare Coating

All the GM50D Series Offers higher haze panal that helps with reflections without notably affecting the image quality.

By reducing glare, anti-glare coatings enhance the visibility of the display's content. This is crucial for digital signage, as it ensures that passersby and viewers can clearly see and read the information, advertisements, or messages being displayed. Improved visibility can lead to better communication and engagement.

High Brightness

In outdoor settings or indoor environments with lots of ambient light, such as shopping malls, airports, or storefronts with large windows, high-brightness displays are essential. The GM50D Series displays deliver 500 nits brightness so they can overcome the challenges posed by direct sunlight or strong indoor lighting, ensuring that the content remains visible and legible even in bright conditions.



Android 11 - A Safer and Enhanced Experience

Android 11 works to keep your data safe and secure. With Android 11, you have more control over what information apps can and can't access.Devices that work better together,enhance your messaging, audio and multitasking experiences.



Clean Cable Solutions

The integrated cable holder hides cables and keeps the back of the display tidy and uncluttered. This reduces visual distractions that can get in the way of your viewing experience.



Narrow Bezel

The narrow bezel on the GM50D series digital signage display enhances the visual appeal, functionality, and effectiveness of the display in commercial applications. It allows for more seamless content presentation, improved aesthetics, and greater flexibility in designing engaging displays.

For presentations, conferences, or digital signage setups that require multiple screens, a narrow bezel ensures that the transition between different screens is seamless. It helps maintain the continuity of content across multiple displays, making it easier for viewers to follow presentations or messages.



Wireless Screen Sharing with Quad Split Screen

With Hisense GM50D series, you can eliminate the need for physical cables, adapters, and complex setup processes. Users can quickly and easily connect their devices (such as laptops, smartphones, or tablets) to the GM50D series digital signage displays without dealing with cable management, making it a user-friendly option.

Software casting support quad split screen enhancing the usability and versatility our signage displays, making them more interactive, engaging and convenient for both presenters and viewers.





The Complete Solution

Intelligent Content Management

Effortlessly manage, customize and deliver your message with our intuitive CMS platform. Streamline content creation and engage your audience with our powerful, user-friendly platform.



Creation







Dynamic Scheduling

Publishing

Enterprise-Grade Device Management

Empower your business with remote monitoring and control of displays on an installation. Safeguard your digital content with the robust security features of VisionInfo. Protect your displays and marketing content from cyber threats, ensure data privacy, and enjoy total peace of mind.







Complete Control



Notifications

Enhanced Data Management

Unlock the power of data with our advanced analytics and reporting feature within VisonInfo. Gain valuable insights, make data-driven decisions, and maximize the performance of your content.








Analysis





Mobile Device Management

- View the status of remote displays online/offline, CPU and memory running status
- Real-time display control power off, screen sleep/ wake up, reboot, switch signal source, screen lock/ unlock, USB disable/enable
- Remote desktop real-time monitoring
- Scheduled tasks to control displays power On/ off, screen sleep/wake up
- Remote software management APP installation and uninstallation, remote OS Upgrade
- Display usage statistics





Learn More: www.hisense-b2b.com | Contact Us: sales@hisense-b2b.com

VisionInfo

Flexible and Scalable Solutions

anywhere.

16,55,555,555,545,545,547,647,647,647,6

Why Choose VisionInfo for the GM50D Series

VisionInfo from Hisense is our cloud-based digital signage

software which is flexible, cost-effective, and infinitely scalable for users. VisionInfo includes a comprehensive CMS solution and advanced remote display management features. It provides users the freedom to edit and publish content while ensuring it looks great across all displays in a system. It is a powerful, effective and easy to use tool to manage content and control your displays at anytime from

Key Features

F B O 4

- Web browser editor UI
- Drag-and-drop visual editor
- Supports website integration
- Supports live streams
- Supports Office documents and PDF's
- Supports Widgets

- 4K resolution playback
- Offline content playback
- Program preview and publish approval
- Advanced program scheduler
- Custom template layouts
- Playback statistics



Learn More: www.hisense-b2b.com | Contact Us: sales@hisense-b2b.com

Specifications

Model	43GM50D	50GM50D	55GM50D	65GM50D	75GM50D	86GM50D
Backlight Type	DLED	DLED	DLED	DLED	DLED	DLED
Туре	ADS	VA	ADS	ADS	ADS	ADS
Size	43"	50"	55"	65"	75"	86"
Resolution	3840 x 2160					
Refresh rate	60Hz	60Hz	60Hz	60Hz	60Hz	60Hz
Color Depth	1.07G (8 Bits+FRC)					
Brightness(Typ.)	500 nits					
Contrast Ratio(Typ.)	1200:1	5000:1	1200:1	1200:1	1200:1	1200:1
Response Time(Typ.)	8ms	8ms	8ms	8ms	8ms	8ms
Viewing Angle(Min.)	178°/178°	178°/178°	178°/178°	178°/178°	178°/178°	178°/178°
Color Gamut(Typ.)	72% NTSC	DCI-P3 92%	72% NTSC	72% NTSC	72% NTSC	72% NTSC
Haze	25%	25%	25%	25%	25%	25%
Orientation	Landscape & Portrait					
Lifetime	up to 50,000 hrs					
Operation Hours	7Day x 18Hour					

System

Operating System	Android 11	Android 11	Android 11	Android 11	Android 11	Android 11
Processor CPU	ARM Cortex-A55 Quad core	ARM Cortex-A55 Quad core	ARM Cortex-A55 Quad core	ARM Cortex-A55 Quad core	ARM Cortex-A55 Quad core	ARM Cortex-A55 Quad core
Processor GPU	Mali-G52	Mali-G52	Mali-G52	Mali-G52	Mali-G52	Mali-G52
Memory	3G DDR4	3G DDR4	3G DDR4	3G DDR4	3G DDR4	3G DDR4
Storage	32G EMMC	32G EMMC	32G EMMC	32G EMMC	32G EMMC	32G EMMC
Language						

Connectivity

WI-FI	2.4/5.0GHz du-					
	al,802.11a/b/g/n/ac	al,802.11a/b/g/n/ac	al,802.11a/b/g/n/ac	al,802.11a/b/g/n/ac	al,802.11a/b/g/n/ac	al,802.11a/b/g/n/ac
Bluetooth	BT5.1	BT5.1	BT5.1	BT5.1	BT5.1	BT5.1
Input	HDMI(2.0) x 2					
	DP(1.2a) x 1					
	USB2.0(A) x 1					
	USB3.0(A) x 1					
	RS232(RJ45) x 1	RS232(RJ45) x 1	RS232(RJ45) x 1	RS232(R)45) x 1	RS232(RJ45) x 1	RS232(RJ45) x 1
	LAN(RJ45) x 1	LAN(RJ45) x 1	LAN(RJ45) x 1	LAN(R)45) x 1	LAN(RJ45) x 1	LAN(RJ45) x 1
Output	HDMI x 1					
	Audio(3.5mm) x 1					
	RS232(RJ45) x 1					

Physical

Bezel Color	Black	Black	Black	Black	Black	Black
Set Dimension (W×H×D)	970.4 x 557.5 x 62.8mm 38.20 x 21.9 x 2.5inch	1124.1 x 644.2 x 62.5mm 44.26 x 25.36 x 2.46inch	1239.7 x 710.2 x 63.3mm 48.8 x 28 x 2.5inch	1458.9 x 832.8 x 63.7mm 57.4 x 32.8 x 2.5inch	1675.3 x 955.1 x 63.7mm 66 x 37.6 x 2.5inch	1926.6 x 1095.5 x 64.2mm 75.9 x 43.1 x 2.5inch
Bezel width(T/L/R/B)	10.1mm(T/L/R), 10.3mm(B)	10.4mm(T/L/R), 11.1mm(B)	10.1mm(T/L/R), 10.6mm(B)	10.4mm(T/L/R), 10.9mm(B)	10.3mm(T/L/R), 10.8mm(B)	10.3mm(T/L/R), 10.8mm(B)
Net Weight	8.5kg / 18.7lbs	11kg / 24.3lbs	13.9kg / 30.6lbs	21.5kg / 47.4lbs	29kg / 63.9lbs	38.2kg / 84.2lbs
Packing Dimension (W×H×D)	1092 x 663 x 145mm 43 x 26.1 x 5.7inch	1251 x 777 x 154mm 49.2 x 30.6 x 6.1inch	1387 x 838 x 159mm 54.6 x 33 x 6.3inch	1629 x 997 x 160mm 64.1 x 39.0 x 6.3inch	1850 x 1150 x 211mm 72.8 x 45.3 x 8.3inch	2117 x 1298 x 269mm 83.3 x 51.1 x 10.6inch
Gross Weight	12.5kg / 27.56lbs	16.2kg / 35.7lbs	19.5kg / 43lbs	30kg / 66.15lbs	41.6kg / 91.7lbs	59.5kg / 131.2lbs
VESA Mount	300mm x 300mm	300mm x 300mm	300mm x 300mm	400mm x 400mm	600mm x 400mm	600mm x 400mm

^{*} Product specifications may vary per region, and specifications are subject to change. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.

Power

Model	43GM50D	50GM50D	55GM50D	65GM50D	75GM50D	86GM50D
Power Supply	AC 100~240V (50/60Hz)	AC 100~240V (50/60Hz)	AC 100~240V (50/60Hz)	AC 100~240V (50/60Hz)	AC 100~240V (50/60Hz)	AC 100~240V (50/60Hz)
Power Consumption (Typ.)	80W	100W	115W	145W	175W	200W
Power Consumption (Max.)	120W	150W	190W	210W	265W	325W
Standby Consumption	<0.5W (Standby Mode)	<0.5W (Standby Mode)	<0.5W (Standby Mode)	<0.5W (Standby Mode)	<0.5W (Standby Mode)	<0.5W (Standby Mode)
Speaker						
Built in speaker	10W x 2	10W x 2	10W x 2	10W x 2	10W x 2	10W x 2
Environment						
Operating Temperature	0°~40°C	0°~40°C	0°~40°C	0°~40°C	0°~40°C	0°~40°C
Operating Humidity	10%~80% Non-Condensing	10%~80% Non-Condensing	10%~80%	10%~80% Non-Condensing	10%~80% Non-Condensing	10%~80%


What's in the box

	Quick Setup Guide
	Warranty Card
Standard	Power Cord
	Remote Control
	Battery (AAA) x 2
	RS232 Converter Cable


Certification

Standard Certification	CCC/CB/CE/FCC/cTUVus/UKCA/CEC/ERP
Safety	62368-1
Enviroment	Energy Star 8.0
IP Rating	IP5X














43" 970.4 x 557.5 x 62.8mm / 38.20 x 21.9 x 2.5inch 8.5kg / 18.7lbs




55" 1239.7 x 710.2 x 63.3mm / 48.8 x 28 x 2.5inch 13.9kg / 30.6lbs




75" 1675.3 x 955.1 x 63.7mm / 66 x 37.6 x 2.5inch 29kg / 63.9lbs



50" 1124.1 x 644.3 x 62.5mm / 44.26 x 25.36 x 2.46inch 11kg / 24.3lbs



65" 1458.9 x 832.8 x 63.7mm / 57.4 x 32.8 x 2.5inch 21.5kg / 47.4lbs



86" 1926.6 x 1095.5 x 64.2mm / 75.9 x 43.1 x 2.5inch 38.2kg / 84.2lbs

