Hisense



75DM66D 75" 4K UHD DIGITAL SIGNAGE DISPLAY

Hisense Digital Signage is designed to serve multiple business applications: public spaces, transportation systems, museums, stadiums, retail stores, hotels, restaurants and corporate buildings. With DM series, it delivers powerful engagement from any devices, boost business with real-time updates, data-driven insights and visually appealing content, manage and control devices at anytime from anywhere, and simplify the cable management by conecting a series of displays to a single video output.

Highlights



Narrow Bezel

With a narrow bezel and symmetrical design, the display can be easily integrated into any environment. All terminals face outwards, ensuring the display hangs flush against the wall which saves space and facilitates installation.



Clean Cable Solution

The integrated cable holder hides cables and keeps the back of the display tidy and uncluttered. This reduces visual distractions that can get in the way of your viewing experience.



Wireless Screen Sharing

Everthing you need for screen sharing solutions. ScreenShare is a in house built-in screen sharing application that enables the screen sharing wirelessly and seemlessly from anywhere and from any devices.



Mobile Device Management

VisionInfo is a cloud-based device managemet software that offers end-to-end device management and control through all devices. It is a powerful, effective and easy to use tool to control your devices at anytime from anywhere.







Specification	subject to	change	August 2023
opeenication	Jubject to	change	1, 10, 2023



Android 11

Android 11 works to keep your data safe and secure. With Android 11, you have more control over what information apps can and can't access. Devices that work better together, enhance your messaging, audio and multitasking experiences.



Anti-glare Coating

All DM Series displays offer higher haze panels that help reduce reflections without adversley affecting the image quality. Anti-glare coatings can also improve the perceived contrast of the display.

Smart Power

The backlight intensity can be controlled and pre-set by the system to reduce the power consumption, ENERGY STAR-certified, the display helps you protect the environment and save costs.



Conformal Coating

Electronic components are completely protected from the environmental factors like moisture, dust, salt, chemicals, temperature changes and mechanical abrasion.

Hisense

Specifications

Digital Display Panel

Backlight Type	DLED
Туре	ADS
Size	75″
Resolution	3840 x 2160
Refresh rate	60Hz
Color Depth	1.07G (8 Bits+FRC)
Brightness(Typ.)	500 nits
Contrast Ratio(Typ.)	1200:1
Response Time(Typ.)	8ms
Viewing Angle(Min.)	178°/178°
Color Gamut(Typ.)	72% NTSC
Haze	25%
Orientation	Landscape & Portrait
Lifetime	up to 50,000 hrs
Operation Hours	7Day x 24Hour

System

Operating System	Android 11
Processor CPU	ARM Cortex-A55 Quad core
Processor GPU	Mali-G52
Memory	3G DDR4
Storage	32G EMMC
Language	Simplified Chinese/English/French/Ger- man/Polish/Spanish/Russian/Italian/ Finnish/Norwegian/Swedish/Israeli/ Arabic/Thai/Malay/Indonesian

Connectivity

Gross Weight


VESA Mount

WI-FI	2.4/5.0GHz dual,802.11a/b/g/n/ac
Bluetooth	BT5.1
Input	HDMI(2.0) x 2 DP(1.2a) x 1 USB2.0(A) x 1 USB3.0(A) x 1 RS232(RJ45) x 1 LAN(RJ45) x 1
Output	HDMI x 1 Audio(3.5mm) x 1 RS232(RJ45) x 1
Physical	
Bezel Color	Black
Set Dimension(W×H×D)	1675.3 x 955.1 x 63.7mm 66 x 37.6 x 2.5inch
Bezel width(T/L/R/B)	10.3mm(T/L/R), 10.8mm(B)
Net Weight	29kg / 63.9lbs
Packing Dimension (W×H×D)	1850 x 1150 x 211mm 72.8 x 45.3 x 8.3inch

Power		
Power Supply		AC 100~240V (50/60Hz)
Power Consumption (M	ax.)	260W
Standby Consumption		<0.5W (Standby Mode)
Speaker		
Built in speaker		10W x 2
Environment		
Operating Temperature		0°~40°C
Operating Humidity		10%~80% Non-Condensing
What's in the bo	x	
What's in the bo	x	Quick Setup Guide
What's in the bo	x	Quick Setup Guide Warranty Card
What's in the bo	x	
	x	Warranty Card
	x	Warranty Card Power Cord
	x	Warranty Card Power Cord Remote Controller
Standard	x	Warranty Card Power Cord Remote Controller Batteries
		Warranty Card Power Cord Remote Controller Batteries
Standard Certification		Warranty Card Power Cord Remote Controller Batteries RS232(in) Gender
Standard Certification Standard Certification	CCC/CB/CE/FCC/	Warranty Card Power Cord Remote Controller Batteries RS232(in) Gender

Dimensions





Product specifications may vary per region, and specifications are subject to change. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.

Learn More: www.hisense-b2b.com | Contact Us: sales@hisense-b2b.com

41.6kg / 91.7lbs

600mm x 400mm

Hisense COMMERCIAL DISPLAY

📊 @Hisense B2B Europe | @Hisense B2B USA | @Hisense B2B MENA | @Hisense B2B Indonesia | @Hisense B2B South Africa | @Hisense B2B Australia