

EZ Series

General information	Model Number	II-RSS-IREZ2.6
	Pixel Pitch (mm)	2.6mm
	Environment	Indoor
	Physical Density (pixels/m ²)	147,456pixels/m
LED	Configuration	3in1SMD
	Wavelength (pixels/m ²)	R:615-630nm/G:520-535nm/B:465-480nm
Module	Resolution (H x V pixels)	96x96pixels
	Quantity	4
	Dimensions (H x V mm)	250x250mm
	Dimensions (H x V inch)	9,84x9,84inch
	Weight (Kg)	0,59
	Weight (Lb)	1,30
Cabinet	Resolution (H x V pixels)	192x192pixels
	Dimensions (H x V mm)	500x500mm
	Dimensions (H x V inch)	19,69x19,69inch
	Weight (Kg)	5,9
	Weight (Lb)	13,01
	Material	Die-castingMagnesium
	Maintenance Access	Front/Rear
Physical Parameters	Max. Rigging (Panel)	18
Optical Parameters	Brightness (After Calibration/nits)	1000
	Brightness Adjustment	0~100%256levels
	Viewing Angle (°)	160°/160°
	Contrast Ratio	5000:1
	Color Temperature (K)	6500K~3500~9000KAdjustable
	Display Color (T)	4.4T
	Scan Rate	1/24
	Grayscale (Bits)	14bit
Power Supply	Max. Power Consumption (W/Panel)	120w/m ²
	Avg. Power Consumption (W/Panel)	40w/m ²
	Operating Power Source (V)	100-240V AC, 50/60Hz
Control System	Frequency (Hz)	50-60HZ
	Refresh Rate (Hz)	3,840Hz
	Control Mode	Synchronousdisplay
	Signal Input Source	DVI,HDMI,DP,SDI
	Receiving Card	Novastar
	Multiplex/Driver Chips	1:24;ICND2055
	Control Distance (m>km)	Ethernetcable≤120mFiberOptic≤15km
Operating Conditions	Operating Temperature (°C)	-10°C~+45°C
	Operating Humidity (%RH)	10-90%RHNon-condensing
	IP Rating (Front/Rear)	IP30
	LED Lifetime (h)	≥50000h
	Certifications	CE,FCC,ETL,RoHS,REACH