

WP Series		
General information	Model Number	Il-Fiss-lrwp2.5 Lite
	Pixel Pitch (mm)	2,5mm
	Enviroment	Indoor
	Physical Density (pixels/m2)	160.000pixels/□
LED	Configuration	3-in-1 SMD
	Wavelength (pixels/m2)	R:622-629nm/G:520-531nm/B:471-480nm
Module	Resolution (H x V pixels)	120x135pixels
	Quantity	2
	Dimensions (H x V mm)	300x337,5mm
	Dimensions (H x V inch)	11,81x13,29inch
	Weight (Kg)	0,65
	Weight (Lb)	1,43
Cabinet	Resolution (H x V pixels)	240x135pixels
	Dimensions (H x V mm)	600x337,5mm
	Dimensions (H x V inch)	23,62x13,29inch
	Weight (Kg)	5,2
	Weight (Lb)	11,46
	Material	Die-cast Aluminum
	Maintenance Access	Front
Physical Parameters	Max. Rigging (Panel)	/
Optical Parameters	Brightness (After Calibration/nits)	1200
	Brightness Adjustment	0□100% (256 levels)
	Viewing Angle (°)	160°/160°
	Contrast Ratio	5000:1
	Color Temperature (K)	6500K (3000K~10000K adjustable□
	Display Color (T)	4.4T
	Scan Rate	1/30
	Grayscale (Bits)	14bit
Power Supply	Max. Power Consumption (W/Panel)	105w/m2
	Avg. Power Consumption (W/Panel)	35w/m2
	Operating Power Source (V)	100-240V AC, 50/60Hz
Control System	Frequency (Hz)	50-60HZ
	Refresh Rate (Hz)	3.840Hz
	Control Mode	Synchronous Display
	Signal Input Source	DVI. HDMI. DP. SDI. RJ45
	Receiving Card	Novastar
	Multiplex/Driver Chips	ICND2055
	Control Distance (m>km)	Ethernetcable ≤ 120m or Fiber Optic ≤ 15km
Operating Conditions	Operating Temperature (°C)	-10°C~+45°C
	Operating Humidity (%RH)	10-90% RH Non-condensing
	IP Rating (Front/Rear)	IP30
	LED Lifetime (h)	≥50000h
	Certifications	CE. FCC. ETL. CB. RoHS. REACH. WEEE