

#### COMMERCIAL

# Refrigeration Equipment Bottle Cooler with Slide Top, 10 cu.ft, 36" (R600a)



738294 (KCHBC36)

1-door bottle cooler with slide top, 36", R600a refrigerant gas, +33/+41°C, black

# **Short Form Specification**

#### Item No.

Bottle cooler with slide top. Exterior back and side panels in painted steel, exterior bottom panel in galvanized steel, top panel in 304 stainless steel; interior back and side panels in 430 stainless steel, interior bottom panel and worktop in 304 stainless steel. Fin & tube condenser to improve the performances in high temperature environments. Automatic Defrost Cooling System and electronic temperature control.

Vinyl-coated steel adjustable dividers and locking lids.

R600a gas in refrigeration circuit. ETL Safety and Sanitation certified. 3/5 Years warranty.

	X
TEM #	ž
	3
NODEL #	n
NAME #	RC
SIS #	Ä
AIA #	

#### **Main Features**

- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Vinyl-Coated Steel adjustable dividers to customize bottle storage effortlessly.
- Locking doors.
- External temperature display.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Cabinet and door insulated with high density polyurethane for low environmetal impact.
- Locking lids.

### Construction

- CFC and HCFC free (ecological refrigerant type: R600a).
- Pre-wired heavy duty power cord.
- Electronic control to select temperatures.

APPROVAL:



# Refrigeration Equipment Bottle Cooler with Slide Top, 10 cu.ft, 36" (R600a)





Intertek

Intertek

15A 125V NEMA 5-15P

## Electric

Supply voltage: 738294 (KCHBC36) Electrical power, max: Current consumption: Plug type:	115 V/1 ph/60 Hz 0.2 kW 1.5 Amps USA NEMA 5-15P
Capacity:	
Gross capacity:	10 cu.feet
Key Information:	
External dimensions, Width: External dimensions, Depth: External dimensions, Height: Internal Dimensions (depth): Internal Dimensions (height): Shipping height: Shipping weight: Shipping volume:	36 13/16" (935 mm) 27 1/64" (725 mm) 35 " (888 mm) 26 1/16" 22 15/16" 60 3/8" 39 3/4" (1010 mm) 212 lbs (96 kg) 25.25 ft <sup>3</sup> (0.72 m <sup>3</sup> )
Type of external material: Type of internal material: Warranty:	Black Prepainted Steel Stainless Steel 3 / 5 years
<b>Refrigeration Data</b>	
Compressor Horsepower: Refrigerant type:	1/6 B600a

oomprossor norsepower.	1/0
Refrigerant type:	R600a
Refrigerant weight:	100 g
Operating temperature min.:	32 °F
Operating temperature max.:	41 °F
Condenser type:	Fin & tube



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.