COMMERCIAL

Refrigeration Equipment Merchandiser Refrigerator, 12 cu.ft - 1 Glass Door, black (R290)

ITEM #		
MODEL #		
NAME #		
SIS #		
ΔΙΔ #		



738247 (KCHGM12R)

1-glass door merchandiser refrigerator, black, 12 cubic feet, R290 refrigerant gas, +33/+41°F

Short Form Specification

Item No.

1-glass door refrigerator with exterior back and bottom panel in galvanized steel, exterior side and top in painted steel; interior back, side top and bottom panels in 304 stainless steel. Electronic control.

R290 gas in refrigeration circuit.

ETL Safety and Sanitation certified.

3/5 Years warranty.

Main Features

- External temperature display.
- Removable door gasket for easy cleaning operations.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) CFC and HCFC free.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- · Heavy duty Vinyl coated steel shelves.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Cabinet and door insulated with high density polyurethane for low environmetal impact.
- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion
- Interior LED light to save energy and for best internal visibility.

Construction

- Lockable door.
- Electronic control to select temperatures.
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Magnetic door gasket removable without tools for easy cleaning.

Optional Accessories

•	
shelf clips	PNC 880611
•	

APPROVAL:



Refrigeration Equipment Merchandiser Refrigerator, 12 cu.ft - 1 Glass Door, black (R290)

10.8"-275mm 60.2"-1670mm 65.8"-1670mm

49"-1244mm 26"-660mm 24"-610mm EI = Electrical connection

Electric

Front

Supply voltage:

738247 (KCHGM12R) 115 V/1 ph/60 Hz

Electrical power, max: 0.3 kW
Current consumption: 3 Amps

Plug type: USA NEMA 5-15P

Key Information:

Capacity (Cu.Ft.)12Door hinges:Right SideExternal dimensions, Width:25 " (635 mm)External dimensions, Depth:26 " (660 mm)External dimensions, Height:65 3/4" (1670 mm)

Number and type of doors: 1 Glass Internal Dimensions (depth): 46 1/16" Internal Dimensions (height): 18 5/16" Internal Dimensions (width): 18 7/8"

Number and type of grids

 (included):
 4 - Vinyl-Coated Steel

 Shipping height:
 68 11/16" (1745 mm)

 Shipping weight:
 254 lbs (115 kg)

 Shipping volume:
 30.57 ft³ (0.87 m³)

 Type of external material:
 Black Prepainted Steel

 Type of internal material:
 White Prepainted Aluminium

Warranty: 3 / 5 years

Refrigeration Data

Compressor Horsepower:1/5Refrigerant type:R290Refrigerant weight:85 gOperating temperature min.:32 °FOperating temperature max.:41 °FCondenser type:Fin & tubeDefrost type:Auto Defrost







