



KRAMER

C-GMA/GMA

15-pin HD & 3.5mm Stereo Audio Cable

| VGA/UXGA - 15-pin HD



Kramer's C-GMA/GMA is a high-performance cable with male 15-pin HD and 3.5mm stereo audio connectors at each end. It is perfect for computer graphics video to display installations that require an audio signal as well

FEATURES

Quality Construction - Constructed using our rugged and flexible 14-conductor cable

Easy Connection - Pre-terminated with molded 15-pin HD connectors (male to male), gold-plated pins and thumbscrews and a 3.5mm stereo mini jack

Easy Installation - Audio leads extend 24in (61cm) beyond the 15-pin HD head at one end, and 20cm (8in) at the other

All Pins Connected for DDC2 and EDID Support

Varied Selection of Lengths - Available in versions of 3 to 75ft (0.9 to 22.9m)

Cable Specs - For detailed cable specs, see Kramer BC-3X2T7S



TECHNICAL SPECIFICATIONS

Attenuation (dB/100 ft.):	-0.5dB @1MHz -1.3dB @5MHz -1.9dB @10MHz -4.0dB @50MHz -5.7dB @100MHz -8.0dB @180MHz -14.0dB @400MHz
Conductor:	26 AWG 7/34 tinned copper 26 AWG 7/34 tinned copper
Dielectric:	Foam polyethylene with red, green, blue color coding 0.076in (1.95mm)
Shield:	(A) 90% spiral 38 AWG tinned copper. (B) Aluminum foil/Mylar 25% overlap rate (A) 85% braid 36 AWG tinned copper. (B) Mylar 25% overlap rate (A) 85% braid 36 AWG tinned copper. (B) Aluminum foil/Mylar 25% overlap rate
Inner Jacket:	PVC
Jacket Colors:	Black White & white/black, red & red/black Red, orange, brown, yellow, black, red/black
Center Conductor:	0.019in (0.48mm)
Individual Coax:	0.102in (2.6mm)
Impedance:	75Ω
DC Resistance:	45Ω per 1000ft, 148Ω per km
Capacitance:	17.3pF per foot, 57pF per meter
Temperature:	-4° to 167°F (-20° to 75°C)
Jacket:	HD polyethylene HD polyethylene
Diameter:	0.34in (0.88mm) 0.34in (0.88mm)
Conductors:	26 AWG 7/34 tinned copper
Outer Jacket:	PVC
Outer Jacket Color:	Dark gray with white lettering
Outer Diameter:	0.393in (10.0mm)
UL:	CL2
CSA:	C(UL) CL2



KRAMER

CONFIGURATIONS

C-GMA/GMA-3	15-pin HD (M) to 15-pin HD (M) & 3.5mm Stereo Audio Cable
C-GMA/GMA-6	15-pin HD (M) to 15-pin HD (M) & 3.5mm Stereo Audio Cable
C-GMA/GMA-10	15-pin HD (M) to 15-pin HD (M) & 3.5mm Stereo Audio Cable
C-GMA/GMA-15	15-pin HD (M) to 15-pin HD (M) & 3.5mm Stereo Audio Cable
C-GMA/GMA-25	15-pin HD (M) to 15-pin HD (M) & 3.5mm Stereo Audio Cable
C-GMA/GMA-35	15-pin HD (M) to 15-pin HD (M) & 3.5mm Stereo Audio Cable
C-GMA/GMA-50	15-pin HD (M) to 15-pin HD (M) & 3.5mm Stereo Audio Cable
C-GMA/GMA-75	15-pin HD (M) to 15-pin HD (M) & 3.5mm Stereo Audio Cable