



FC-340S

3G HD-SDI Scaler/Embedder/Scan Converter

| 3G HD-SDI - BNC | Ethernet - RJ-45



The FC-340S is a broadcast-quality video scaler and audio embedder/de-embedder for digital signals up to 3G HD-SDI. The unit inputs SDI and AES/3id signals and simultaneously outputs two SDI and composite video signals while the audio embedded in the SDI input signal is output to both AES/3id and balanced stereo audio outputs

FEATURES

Max. Data Rate - 3Gbps

HDTV Compatible

Multi-Standard Operation - SDI (SMPTE 259M), HD-SDI (SMPTE 292M) and 3G HD-SDI (SMPTE 424M)

Looping Video Input

Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances

Embedding Options - Selects embedded audio or embeds two independent audio groups

Flexible Control Options - Front panel with 2-row LCD, Ethernet & RS-232



KRAMER

TECHNICAL SPECIFICATIONS

DIGITAL INPUTS:	1 SD/HD/3G HD-SDI with loop, 75Ω on BNC connectors; 2 AES-3id audio on BNC connectors
DIGITAL OUTPUTS:	2 SD/HD/3G HD-SDI, 75Ω on BNC connectors; 2 AES-3id audio on BNC connectors
ANALOG OUTPUTS:	1 composite video on a BNC connector, PAL/NTSC (according to output frame rate); 2 balanced stereo audio on 5-pin terminal blocks
MAX. DIGITAL VIDEO INPUT/OUTPUT LEVEL:	800mVpp/75Ω
SAMPLE CONVERSION RATE:	48kHz (digital audio)
BANDWIDTH:	20kHz (analog audio)
INPUT RESOLUTIONS:	480i @59.94, 576i @50, 720p @59.94/60/50, 1080i @59.94/60/50, 1080p @29.97/30/23.98/24, 23.98sF/24sF, 1080p @59.94/60/50
OUTPUT RESOLUTIONS:	480i @59.94, 576i @50, 72p @59.94/60/50, 1080i @59.94/60/50, 1080p @59.94/60/50
POWER CONSUMPTION:	12V DC, 1A
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
INCLUDED ACCESSORIES:	Power supply
PRODUCT DIMENSION:	21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72") W, D, H
PRODUCT WEIGHT:	1.0kg (2.2lbs) approx
SHIPPING DIMENSION:	35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H
SHIPPING WEIGHT:	1.6kg (3.6lbs) approx

