

OC-4

4-Channel Video/Sync Optical Isolator



The OC-4 is a high-performance optical isolator for video or sync signals. It provides complete isolation between devices to eliminate video hum, ground loops and DC offsets that can degrade picture quality

FEATURES

Bandwidth - 20MHz (-3dB)

Channels - 4

Opto Isolator Circuitry - Extremely linear response and wide frequency range compared to traditional transformer based units

Level (Gain) and EQ (Peaking) Controls

Floating Ground Selection - Input, output, both, or none



TECHNICAL SPECIFICATIONS

INPUTS: 4 composite video, $1Vpp/75\Omega$ on BNC connectors

OUTPUTS: 4 composite video, $1Vpp/75\Omega$ on BNC connectors

BANDWIDTH (-3dB): 20MHz

VIDEO S/N RATIO: 69dB

POWER CONSUMPTION: 230V AC, 50/60Hz, (115V AC, USA), 17VA max

INCLUDED

ACCESSORIES:

Power cord

PRODUCT

19" x 7.20 x 1U (43.6cm x 18.30cm 4.36cm) W, D, H

DIMENSION:

19" x 7.20 x 1U (43.6cm x 18.30cm 4.36cm) W, D, H

PRODUCT WEIGHT: 0.0kg (0.0lbs) approx

3.0kg (6.6lbs) approx

SHIPPING

55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H

DIMENSION:

55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H

SHIPPING WEIGHT: 3.8kg (8.3lbs) approx

3.8kg (8.3lbs) approx

