



## PT-571HDCP

### DVI over Twisted Pair Transmitter



The **PT-571HDCP** is a twisted-pair transmitter for DVI signals. The **PT-571HDCP** converts the DVI to twisted pair signal and the **PT-572HDCP** converts the twisted pair signal back to a DVI signal.

### FEATURES

- Max. Data Rate - 1.65Gbps.
- HDTV Compatible.
- HDCP Compliant.
- System Range - Up to 90m (295ft) at SXGA, or up to 30m (98ft) at UXGA on shielded BC-DGKat524 cable.  
Up to 90m (295ft) at SXGA, or up to 70m (230ft) at UXGA on shielded BC-DGKat623 cable.  
Up to 100m (330ft) at SXGA, or up to 80m (265ft) at UXGA on shielded BC-DGKat723 cable.
- Cable - Requires shielded twisted pair (STP) cable. For optimum range and performance use, use Kramer's BC-DGKat524, BC-DGKat623 and BC-DGKat723 cables. Note that the transmission range depends on the signal resolution, graphics card and display used. The distance using non-Kramer CAT 5, CAT 6, and CAT 7 cables may not reach these ranges. Use only shielded cable where both ends of the shield are soldered to ground.
- EDID PassThru - Passes EDID/HDCP signals from source to display.
- Power Connect™ System - A single connection to the transmitter powers both units when the devices are within 150ft (50m) of each other.
- Ultra-Compact PicoTOOLS™ - 4 units can be rack mounted side-by-side in a 1U rack space with the optional RK-4PT rack adapter.



## PT-571HDCP

---

### TECHNICAL SPECIFICATIONS

---

INPUTS:	1 DVI, 1.2Vpp on a DVI Molex 24-pin female connector.
OUTPUTS:	1 CAT 5 OUT on an RJ-45 connector.
BANDWIDTH:	Supports up to 1.65Gbps.
POWER SOURCE:	12V DC, 250mA (transmitter and receiver together).
DIMENSIONS:	6.2cm x 5.2cm x 2.4cm (2.4" x 2.1" x 1") W, D, H.
WEIGHT:	0.14kg (0.3lbs).
ACCESSORIES:	Power supply, mounting bracket.
OPTIONS:	RK-4PT 19" rack adapter, Kramer DVI cables and BC-DGKat524 (CAT 5 24AWG) and BC-DGKat623 (CAT 6 23AWG) cables.