



SPK-C800-PRO

Complete K-coverage ESD™ (Equal Sound Dispersion) Ceiling Speaker

| Speakers



The SPK-C800-PRO is an innovative, patent pending Kramer Complete K-coverage ESD™ ceiling speaker. It is the only speaker in the industry with built-in stereo separation. Constructed with a central driver and four pivoting tweeters in a sealed enclosure, the Kramer Complete K-coverage ESD™ provides unmatched sound response for both voice and music in a suspended ceiling device for the professional market

FEATURES

Complete K-coverage ESD™ - Patent pending design with 4 pivoting tweeters direct the sound, based on the room environment, for equal sound dispersion (ESD)

Wide Sound Dispersion - 180° range

Minimizes Speaker Installation - One Kramer ESD speaker replaces multiple standard speakers for quick and easy installation

Excellent Bass Response - Optimized for music and high-quality voice reproduction

Tweeters - 4 pivoting 3/4" 6Ω with silk domes

Woofer - 8" 8Ω polypropylene cone

Power Rating - 40W RMS

Smooth Frequency Response

Depth - Shallow 4" (approx. 100mm)

RoHS Compliant

UL Listed - UL2043 – Fire test for heat and visible smoke release for discrete products and their accessories installed in air-handling spaces

Choice of Models - Size: full tile: 60cm x 60cm (24" x 24") or half tile: 30cm x 60cm (12" x 12"), stereo or mono

Accessories - Installation bracket (for half-tile only)

Package - 1 speaker, template and user manual



KRAMER

TECHNICAL SPECIFICATIONS

INPUT POWER:	40W RMS, 110W continuous program
NOMINAL SENSITIVITY:	87dB SPL @1m
CROSSOVER FREQUENCY:	2kHz
MEAN SPL:	87dB +/-1dB @1W-1m
FREQUENCY RANGE:	Nominal: 80Hz-20kHz, max: 60Hz-20kHz
SPEAKER TYPE:	Two-way closed-back ceiling speaker
WOOFER:	8" (203mm) polypropylene cone with rubber surround
TWEETER:	4 x 3/4" (19mm) silk dome pivoting tweeter
IMPEDANCE:	Woofer: 8 Ω ; tweeter: 6 Ω
SENSITIVITY:	87dB SPL @1W, 1m
INCLUDED ACCESSORIES:	Ceiling mounting bracket for 30cm x 60cm



KRAMER

CONFIGURATIONS

SPK-C812	Complete K-coverage ESD® Ceiling Speakers Full-tile Stereo
SPK-C814	Complete K-coverage ESD® Ceiling Speakers Half-tile Stereo
SPK-C815	Complete K-coverage ESD® Ceiling Speakers Half-tile Mono
SPK-C820	Complete K-coverage ESD® Ceiling Speaker – 595m Stereo