



KRAMER

VM-400HDCPxI

1:4 4K60 4:2:0 DVI DA

| DVI | HDCP Compliant | 4K/60 UHD (4:2:0)



The VM400HDCPxI is a 4K@60Hz (4:2:0) 1:4 distribution amplifier for HDMI signals via singlelink DVI. It takes one DVI input, equalizes and reclocks the signal and distributes it to four identical outputs. With the appropriate adapter, it distributes signals having resolutions up to 4K@60Hz (4:2:0), WUXGA and 1080p

FEATURES

Max. Data Rate - 10.2Gbps (3.4Gbps per graphic channel)

Max. Resolution - 4K@60 (4:2:0), WUXGA and 1080p

HDCP Compliance

Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal integrity to travel longer distances

I-EDIDPro™ Kramer Intelligent EDID Processing™ - An intelligent EDID handling and processing algorithm that ensures Plug and Play operation for HDMI systems

Default EDID - For fast and efficient connection of the unit

3D Pass-Through

USB Port - For firmware upgrading



KRAMER

TECHNICAL SPECIFICATIONS

INPUT:	1 DVII connector
OUTPUTS:	4 DVII connectors
PORT:	1 USB for firmware upgrade
MAX. DATA RATE:	10.2Gbps (3.4Gbps per graphic channel)
STANDARDS COMPLIANCE:	Supports HDMI and HDCP
CONTROLS:	EDID Setup button
INDICATOR LEDs:	IN, OUT 1 to 4 LEDs
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	40° to +70°C (40° to 158°F)
HUMIDITY:	10% to 90%, RHL noncondensing
PRODUCT DIMENSION:	18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00") W, D, H
PRODUCT WEIGHT:	0.5kg (1.0lbs) approx
SHIPPING DIMENSION:	34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H
SHIPPING WEIGHT:	1.0kg (2.2lbs) approx
POWER CONSUMPTION:	5V DC, 1.1A
INCLUDED ACCESSORIES:	Power supply