

PANEL

Screen Size	32"
Panel Technology	IPS
Native Resolution	1,920 x 1,080 (FHD)
Brightness (nit)	500
Contrast Ratio	1,000:1
Color gamut	NTSC 72%
Viewing Angle (H x V)	178 x 178
Color Depth	8bit, 16.7 Million colors
Response Time	9ms (G to G)
Surface Treatment (Haze)	Haze 12%
Life time	50,000Hrs (Min.)
Operation Hours (Hours / Day)	24 / 7
Portrait / Landscape	Yes / Yes

CONNECTIVITY

Input	Digital (HDMI(2), HDCP 1.4), RS232C IN, RJ45(LAN), IR IN, USB2.0 Type A(1)
Output	Audio Out, USB2.0 Type B(1)

MECHANICAL SPECIFICATION

Bezel Color	Black
Bezel Width	11.3/11.3/11.3/13.2 mm
Weight (Head)	5.8 kg
Monitor Dimensions (W × H × D)	723.0 x 419.4 x 39.1 mm
Carton Dimensions (W × H × D)	812 x 510 x 142 mm
VESA™ Standard Mount Interface	200 x 200

KEY FEATURE(HARDWARE)

Internal Memory	8GB (System 5GB + Available 2.48GB)
Temperature Sensor	Yes
Acceleration(Gyro) Sensor	Yes

KEY FEATURE(SOFTWARE)

webOS ver.	webOS 6.0
Embedded CMS	Local Contents Scheduling, Group Manager
USB Plug & Play	Yes
Fail over	Yes
Background Image	Booting Logo Image, No Signal Image
Video Tag	Yes
Play via URL	Yes
Screen Rotation	Yes

Gapless Playback	Yes
Setting Data Cloning	Yes
SNMP	Yes
ISM Method	Yes
Status Mailing	Yes
Control Manager	Yes
Cisco Certification	Yes
Crestron Connected	Yes
Power	Smart Energy Saving, PM mode, Wake on LAN, Network Ready
HDMI-CEC	Yes
SI Server Setting	Yes
webRTC	Yes
Pro:Idiom	Yes

ENVIRONMENT CONDITIONS

Operation Temperature	0°C to 40°C
Operation Humidity	10 % to 80 %

POWER

Power Supply	AC 100-240V~, 50/60Hz
Power Type	Built-In Power

POWER CONSUMPTION

Typ.	48 W
Max.	65 W
BTU (British Thermal Unit)	1 64 BTU/Hr(Typ.), 222 BTU/Hr(Max.)
Smart Energy Saving (70%)	34 W
DPM	0.5 W↓
Power off	0.5 W↓

CERTIFICATION

Safety	CB / NRTL
EMC	FCC Class "A" / CE / KC
ErP / Energy Star	N/A / Yes

SOFTWARE COMPATIBILITY

SuperSign CMS	Yes
SuperSign Control+	Yes
SuperSign Cloud	Yes
Mobile CMS	Yes
Connected Care	Yes

ACCESSORY

