

## PANEL

Screen Size	50"
Panel Technology	VA
Back Light Type	Direct
Aspect Ratio	16:9
Native Resolution	3,840 × 2,160 (UHD)
Refresh Rate	60Hz
Brightness	400nit (Typ.)
Contrast Ratio	5,000:1
Dynamic CR	1,000,000:1
Color gamut	DCI 80%
Viewing Angle(H x V)	178x178
Color Depth	1.07G (8bits + FRC)
Response Time	6ms (G to G)
Surface Treatment(Haze)	2%
Life time	30,000Hrs (Min)
Operation Hours (Hours/Day)	16/7
Portrait / Landscape	Yes / Yes

## CONNECTIVITY

<b>Input</b>	HDMI (3, HDCP 2.2/1.4), RS-232C In (4 Pin Phone-jack), RJ45 (LAN), USB 2.0 (2, Type A)
--------------	--

<b>Output</b>	Audio Out, RS-232C Out (4 Pin Phone-jack)
---------------	---

## MECHANICAL SPECIFICATION

<b>Bezel Color</b>	Ashed Blue
--------------------	------------

<b>Bezel Width</b>	Off : 7.3/7.3/7.3/18.4 mm On : 12.8/12.8/12.8/19.9 mm
--------------------	--

<b>Weight(Head)</b>	11.7 kg
---------------------	---------

<b>Packed Weight</b>	14.4 kg
----------------------	---------

<b>Monitor Dimension(W x H x D)</b>	1,121 x 651 x 57.1 mm
-------------------------------------	-----------------------

<b>Carton Dimensions(W x H x D) (Box outer size)</b>	1,215 x 775 x 152 mm
--	----------------------

<b>VESA™ Standard Mount Interface</b>	200 x 200 mm
---------------------------------------	--------------

## KEY FEATURE

<b>HW</b>	Internal Memory (eMMC) 16 GB, Built-in Wi-Fi, Sensor (Temperature Sensor, Auto Brightness Sensor), Local Key Operation (Power On/Off Only)
-----------	--

<b>SW</b>	webOS 6.0, Embedded CMS (Local Contents Scheduling, Group Manager), USB Plug & Play, Fail Over, Background Image (Booting Logo Image, No Signal Image), Sync Mode (RS-232C Sync, Local Network Sync), Screen Share, Video Tag (4, Max One HDMI Input), Play via URL, Rotation (Screen Rotation, External Input Rotation), Gapless Playback, Tile Mode Setting, Setting Data Cloning, SNMP, ISM Method, Auto Set ID, Status Mailing, Control Manager, 3rd Party Compatibility (Cisco Certi. (TBD, ~ ` 23.7)), Crestron Inside, Power (Smart Energy Saving, PM Mode, Wake on LAN, Network Ready), Beacon, HDMI-CEC 1), SI Sever Setting, webRTC, Pro:Idiom
-----------	--

## ENVIRONMENT CONDITIONS

Operation Temperature	0 °C to 40 °C (Portrait Scene : 0 °C to 35 °C)
-----------------------	--

---

Operation Humidity	10 % to 80 %
--------------------	--------------

---

## POWER

Power Supply	AC 100-240V~, 50/60Hz
--------------	-----------------------

---

Power Type	Built-In Power
------------	----------------

---

## POWER CONSUMPTION

Typ.	90 W
------	------

---

Max.	130 W
------	-------

---

BTU (British Thermal Unit)	307 BTU/Hr(Typ.), 444 BTU/Hr(Max.)
----------------------------	------------------------------------

---

Smart Energy Saving (~70%)	63 W
----------------------------	------

---

DPM	0.5 W
-----	-------

---

Power off	0.5 W
-----------	-------

---

## SOUND

Speaker	Yes (10W x 2)
---------	---------------

---

## CERTIFICATION

Safety	CB / NRTL
--------	-----------

---

EMC	FCC Class "A" / CE
-----	--------------------

---

ErP / Energy Star	Yes / Yes
-------------------	-----------

---

## SOFTWARE COMPATIBILITY

SuperSign CMS	Yes
---------------	-----

---

SuperSign Control+	Yes
--------------------	-----

---

SuperSign WB	Yes
--------------	-----

---

LG ConnectedCare	Yes
------------------	-----

---

## LANGUAGE

OSD	English, French, German, Spanish, Italian, Korean, Chinese(Simplified), Chinese(Original), Portugues(Brazil), Swedish, Finnish, Norwegian, Danish, Russian, Japanese, Portugues(Europe), Dutch, Czech, Greek, Türkçe, Arabic, polski
-----	--

---

## ACCESSORY

Basic	Remote Controller(include battery 2ea), Power Cord, Regulation Book, Phone to D-Sub9 Gender, Cable Holder
-------	---

---