

## PANEL

Screen Size	55" Class (54.64" diagonal)
Panel Technology	M+ (WRGB)
Aspect Ratio	16 : 9
Native Resolution	1,920 x 1,080 (FHD)
Brightness	3,000 cd/m2 (Typ), 2,400 cd/m2 (Min.)
Contrast Ratio (Typ.)	1,000:1
Dynamic CR	500,000:1
Lifetime	50,000 Hrs
Operation Hours	24Hrs
Orientation	Landscape & Portrait
Viewing Angle (H x V)	178 x 178
Surface Treatment	Anti Glare & Low Reflection (Haze 3%), QWP

## CONNECTIVITY

External Control	RS232C In/Out, RJ45 In, IR Receiver In, Pixel Sensor In
Input	HDMI(2), DP, DVI-D, Audio, USB
Output	DP, External Speaker Out (L/R)

## PHYSICAL SPECIFICATION

<b>Bezel Width</b>	9.9 mm (L/R), 12 mm (T/B)
<b>Dimensions (w/o Stand)(W x H x D)</b>	48.6" x 27.9" x 4.2" 1,235.5 x 709.4 x 106.8 mm
<b>Weight (Head)</b>	58.4 lbs / 26.5 kg
<b>Dimensions (Carton) (W x H x D)</b>	52.9" x 32.3" x 9.3" 1,344 x 820 x 236 mm
<b>Weight (Packed)</b>	71.2 lbs / 32.3 kg
<b>VESA™ Standard Mount Interface</b>	600 x 400mm

## SPECIAL FEATURES

<b>Yes</b>	Temperature Sensor, Auto Brightness Sensor, Cooling Fan, Tile Mode (up to 15 x 15), Natural mode@Tile Mode, Source Selection, ISM Method, DPM Select, Energy Saving, Smart Energy Saving, File Play with USB, Internal Memory (System 4GB + Available 4GB), Wi-Fi Dongle Ready
------------	--

## ENVIRONMENTAL CONDITIONS

<b>Operating Humidity Range</b>	10% to 80%
<b>Operating Temperature Range</b>	0°C to 50°C (without Direct Sunlight) 0°C to 40°C (Direct Sunlight)

## POWER

<b>Power Supply</b>	100 -240V~, 50/60Hz
<b>Power Type</b>	Built-In Power
<b>Power Consumption Typ. / Max.</b>	250W (Full White) / 230W (IEC 62087)
<b>Power Consumption (Smart Energy Saving)</b>	120 W

## STANDARD CERTIFICATIONS

<b>EMC</b>	FCC Class "A" / CE / KC
------------	-------------------------

---

<b>Safety</b>	UL Recognized / CB
---------------	--------------------

---

## SOFTWARE COMPATIBILITY

<b>Content Management Software</b>	SuperSign CMS
------------------------------------	---------------

---

## ACCESSORIES

<b>Basic</b>	Remote Controller (2 Batteries Included), Power Cord, IR Extension Cable/PCB, HDMI Cable, Manual (ESG & EIG)
--------------	--

---

<b>Optional</b>	Pixel Sensor (KT-SP0) * Stand is not available
-----------------	--

---