

Tech Spec

- Panel

Screen Size	65
Panel Technology	IPS
Back Light Type	Edge
Aspect Ratio	16
Resolution	3,8
Refresh Rate	60
Brightness (Typ.)	70
Contrast Ratio	1,1
Dynamic CR	1,0
Color gamut	BT
Viewing Angle (H x V)	17
Color Depth	10
Response Time	8 ms
Surface Treatment (Haze)	28

Life Time (Min.)	50
Operation Hours (Hours / Days)	24
Portrait / Landscape	Ye

• Mechanical Specification

Bezel Color	Black
Bezel Width	T/R/L:
Weight (Head)	28.2 Kg
Weight (Head+Stand)	28.8 Kg
Packed Weight	35.0 Kg
Monitor Dimensions (W × H × D)	1,453.3
Monitor Dimensions with Stand (W × H × D)	1,453.3
Carton Dimensions (W × H × D)	1,600.0
VESA™ Standard Mount Interface	300 × 3

• Special Feature

Tilt (Facedown)	Yes (Max 30° degree, 30°C temperature)
IP Rating	IP5X

• Key Feature (Hardware)

Internal Memory

Wi-Fi

Temperature Sensor

Auto Brightness Sensor

Acceleration(Gyro) Sensor

Local Key Operation

• **Key Feature (Software)**

webOS ver.

webOS 6.0

Embedded CMS

Local Contents Scheduling, Group

USB Plug & Play

Yes

Fail over

Yes

Multi-screen

PIP, PBP (4)

Screen Share

Yes

Background Image

Booting Logo Image, No Signal Im

Sync Mode

RS-232C Sync, Local Network Syn

Video Tag

Yes (4)

Play via URL

Yes

Rotation	Screen Rotation, External Input R
Gapless Playback	Yes
Tile Mode Setting	Yes (Max. 15x15)
Setting Data Cloning	Yes
SNMP	Yes
ISM Method	Yes
Auto Set ID	Yes
Status Mailing	Yes
Control Manager	Yes
3rd Party Compatibility	Crestron Connected
Beacon	Yes
Power	Smart Energy Saving, PM mode, V
HDMI-CEC	Yes
SI Server Setting	Yes
webRTC	Yes
Pro:Idiom	Yes

- [Connectivity](#)

Input HDMI (2, HDMI1/HDMI2 : HDCP 2.2/1.4), DP (1, USB-C(DP
(1, 4pin Phone-jack), RJ45(LAN), IR IN, USB2.0 Type A(1), U

OutputDP Out (1, Input : HDMI1/2/DVI/DP/USB-C/OPS), Audio O

• Environment Conditions

Operation Temperature

Operation Humidity

• Power

Power Supply AC 100-240V~, 50/60Hz

Power Type Built-In Power

• Power Consumption

Typ./Max. 130W / 190W

Smart Energy Saving 91W

DPM 0.5W

Power off 0.5W

BTU (British Thermal Unit) 444 BTU/Hr(Typ)

• OPS Compatibility

OPS Type Compatible

• Software Compatibility

SuperSign CMS Yes

SuperSign Control / Control+	Yes
SuperSign WB	Yes
SuperSign Media Editor	Yes
LG ConnectedCare	Yes
Promota	Yes (New)
Mobile CMS	Yes

- **Sound**

Speaker

- **Certification**

Safety CB / NRTL

EMC FCC Class "A" / CE / KC

ErP Yes (NewErP)

- **Language**

OSD English, French, German, Spanish, Italian, Korean, Chinese (Simplified), Chinese (Traditional), Swedish, Finnish, Norwegian, Danish, Russian, Japanese, Portuguese

- **Accessory**

Basic Remote Controller (include battery 2ea), Power Cord, QSD Cable

Optional Stand (ST-653T), Wall bracket (LSW350B), OPS Kit (KT-C)

