Wash/ No. of

Max R

Water

Tempe

Drying

LG STUDIO

SWWE50N3/SWWG50N3

Front Load 5.0 cu. ft. Washer and 7.4 cu. ft. Dryer Wash Tower

5.0 cu. ft. Washer and 7.4 cu. ft. Dryer Single Unit Wash Tower™ Al Sensor Dry and TurboSteam®

Allergiene® Cycle

AI DD® 2.0 Advanced Washing with Soil Sensor and TurboWash® 360

Manual Dry Times FABRIC CARE FEATURES

TurboWash™ 360 Technology

AI DD™

Washe

Yes

Touch Electronic Center Control® Panel with LCD Display

ezDispense® Automatic Dispenser

Tinted Round Tempered Glass Door

ThinQ® Technology with ThinQ Care

ENERGY STAR® Most Efficient



Yes

Yes (TurboSteam™) Dryer

4 Adjustable Legs

Yes Yes Yes Yes

Electric: 3 Way Venting / Gas: 2 Way Venting

Drye

Yes







		,	
Туре	Front Load Washer	Front Load Dryer	
Capacity (cu.ft.)	5.0 cu. ft. 7.4 cu. ft.		
Color	Noble Steel		
APPEARANCE	Washer	Dryer	
Touch Buttons	Ye	es	
LCD Display	Ye	es	
Center Control™	Yes		
ENERGY	Washer	Dryer	
ENERGY STAR® Qualified	Ye	es	
CEE Tier	Advanced Tier	-	
IMEF	3.1	-	
IWF	2.9	=	
CEF	=	Electric: 3.94 Gas: 3.49	
PROGRAMS	Washer	Dryer	
No. of Programs	12 (+14)	12 (+13)	
	Normal, Al Wash, Bed- ding, Delicates, Towels, Quick Wash, Heavy Duty, Allergiene™, Perm. Press, Tub Clean, Bright Whites™, Sanitary	Normal, AI Dry, Bedding, Delicates, Towels, Quick Dry, Timed Dry, Antibacterial, Perm. Press, Steam Fresh™, Heavy Duty, Air Dry	
OPTIONS	Washer	Dryer	
No. of Options	18	14	
	TurboWash™, Steam, Extra Rinse, Pre- wash, Drum Light, Control Lock, Signal, Wi-Fi/Remote Start, ezDispense™, Cold Wash™, Fresh Care, Delay Wash, Cycle List Edit, ezDispense™ Nozzle Clean, Smart Diagnosis, Cycle Optimization, Brightness, Factory Reset	TurboSteam™, Energy Saver, Low Static, Wrinkle Care, Damp Dry Signal, Drum Light Cycle List Edit, Signal, Smart Diagnosis, Control Lock, Cycle Optimization, Wi-Fi/ Remote Start, Brightness, Factory Reset	
DETAILS	Washer	Dryer	
No. of Wash/Rinse Temps	5	-	

		, .	ranborrasii boo reeiiiiology	103
h Buttons	Ye	25	Steam Technology	Yes
Display	Ye	25	Allergiene™ Cycle	Yes (Cloud Cycle)
er Control™	Ye	25	Sanitary Cycle	Yes
RGY	Washer	Dryer	Al Sensor Dry™	=
RGY STAR® Qualified	Ye	25	Sensor Dry	=
Гier	Advanced Tier 3.1	-	Precise Temperature Control with Variable Heater	-
	2.9	_	Steam Technology	-
	2.3	Electric: 3.94	CONVENIENCE FEATURES	Washer
	=	Gas: 3.49	Vibration sensing (Cabinet	Yes
GRAMS	Washer	Dryer	Vibration sensor)	103
f Programs	12 (+14)	12 (+13)	TrueBalance™ Anti-Vibration System	Yes
	Normal, Al Wash, Bedding, Delicates, Towels, Quick Wash, Heavy Duty, Allergiene™, Perm. Press, Tub	Normal, Al Dry, Bedding, Delicates, Towels, Quick Dry, Timed Dry, Antibacterial, Perm.	4 Tray Dispenser End of Cycle Signal	Prewash, Main Was (with liquid deterge cup), Bleach, Fabri Softener
	Clean, Bright Whites™, Sanitary	Press, Steam Fresh™, Heavy Duty, Air Dry	LoadSense	Yes
ONS	Washer	Dryer Dryer	Soil Level Sense	Yes
f Options	18	14	Control Lock	Yes
	TurboWash™, Steam,		Auto Suds Removal	Yes
	Extra Rinse, Pre-	TurboSteam™, Energy	Leveling Legs	4 Adjustable Legs
	wash, Drum Light, Control Lock, Signal,	Saver, Low Static,	Drum Light	Yes
	Wi-Fi/Remote Start, ezDispense™, Cold	Wrinkle Care, Damp Dry Signal, Drum Light, Cycle List Edit, Signal,	Remaining Time Display/ Status Indicator(s)	Yes
	Wash™, Fresh Care,	Smart Diagnosis,	3 Minute Installation Check	-
	Delay Wash, Cycle List Edit, ezDispense™	Control Lock, Cycle	End of Cycle Signal	-
	Nozzle Clean,	Optimization, Wi-Fi/ Remote Start,	Drum Light	-
	Smart Diagnosis, Cycle Optimization, Brightness, Factory	Brightness, Factory Reset	FlowSense™ Duct Clogging Indicator	=
	Reset		Wrinkle Care Option	=
AILS f Wash/Rinse Temps	Washer 5	Dryer	Venting Option	-
i wasii/itilise teliips	Hot, Very Warm,		ThinQ® TECHNOLOGY	Washer
n/Rinse Temps	Warm, Cool, Cold	-	SmartDiagnosis™ (v3.0)	
f Spin Speeds	5	-	Wi-Fi	
Speeds	High, Medium/High, Medium, Low, No Spin	-	ThinQ Care Remote Start and Cycle	
RPM	1300	=	Monitor	
er Levels	Load Sensing	<u>=</u>	Energy Monitoring	
f Soil Levels	5	=	Tub Clean Coach	Yes
		High, Medium/	MOTOR AND AGITATOR	Washer
erature Settings	-	High, Medium, Low/ Medium,Low	Motor Type	Inverter Direct Driv Motor
ig Levels	-	Very, More, Normal, Less, Damp	Axis	Horizontal

MATERIALS AND FINISHES	Washer	Dryer	
NeveRust™ Stainless Steel Drum	Ye	5	
Control Panel	Plastic		
Top Plate	Steel		
Cabinet	Painted Steel		
Door / Rim	Large Circle (Chrome Rim	
Door Cover	Tinted Round Te	empered Glass	
All Available Colors	Noble	Steel	
CERTIFICATION	Washer	Dryer	
AAFA	Yes	-	
POWER SOURCE	Washer	Dryer	
Ratings	CSA Listed	-	
Electrical Requirements	120V, 10 Amps	-	
Туре	Electric	-	
Ratings	=	CSA Listed	
Electrical Requirements	-	240V, 30 Amps (Electric) / 120V, 15 Amps (Gas)	
Туре	-	Electric / Gas	
BTU Rating	-	Gas: 20,000	
LP Conversion Kit	=	383EEL3002D	
Side Venting Kit	-	3911EZ9131X	
DIMENSIONS	Washer	Dryer	
Product (WxHxD)	27" x 74 3/8	" x 32 3/4"	
Depth with Door Open	58" D with	door open	
Carton (WxHxD)	30 1/16" x 79 11/32" x 33 23/32"		
Weight (Product/Carton)	Electric: 333 lbs. / 368 lbs. / Gas: 336 lbs. / 371 lbs.		
LIMITED WARRANTY	Washer	Dryer	
Parts and Labor	2 Ye	ar	
Drum	3 Ye	ars	
Direct Drive Motor	10 Years	-	
UPC CODES			
SWWE50N3 (Noble Steel)	195174054413		
SWWG50N3 (Noble Steel)	195174054420		



SWWE50N3/SWWG50N3

Laundry Center

QUICK INSTALL & CLEARANCES

For full installation directions/clearances please refer to the corresponding User Manual and Installation Guide.

Ratings Electrical Requirements Type Ratings Electrical Requirements Type BTU Rating LP Conversion Kit Side Venting Kit Rack CERTIFICATION	CSA & UL Listed 120V, 10 Amps Electric	CSA & UL Listed 120V, 15 Amps (Gas) 240V 30 Amps (Electric) Gas / Electric 20,000 Feet 383EEL3002D
Type Ratings Electrical Requirements Type BTU Rating LP Conversion Kit Side Venting Kit Rack		120V, 15 Amps (Gas) 240V 30 Amps (Electric) Gas / Electric 20,000 Feet
Ratings Electrical Requirements Type BTU Rating LP Conversion Kit Side Venting Kit Rack	Electric	120V, 15 Amps (Gas) 240V 30 Amps (Electric) Gas / Electric 20,000 Feet
Electrical Requirements Type BTU Rating LP Conversion Kit Side Venting Kit Rack	- - - -	120V, 15 Amps (Gas) 240V 30 Amps (Electric) Gas / Electric 20,000 Feet
Type BTU Rating LP Conversion Kit Side Venting Kit Rack	- - -	240V 30 Amps (Electric) Gas / Electric 20,000 Feet
BTU Rating LP Conversion Kit Side Venting Kit Rack	- - -	20,000 Feet
LP Conversion Kit Side Venting Kit Rack	_ _	<u>'</u>
Side Venting Kit Rack	_	383EEL3003D
Rack		303LLL3002D
	_	383EEL9001B
CERTIFICATION	_	Yes
	WASHER	DRYER
AAFA	Yes	_
Intertek	es(Sanitary cycle)	Yes(Antibacterial cycle)



