

**Configuration:**

LA-205-01 30 VDC Extension/Replacement Power Supply for LA-140/LT-82 (North America)*

LA-205-02 30 VDC Extension/Replacement Power Supply for LA-140/LT-82 (Asia, UK)*

LA-205-03 30 VDC Extension/Replacement Power Supply for LA-140/LT-82 (Euro)*

LA-205-03 31 VDC Extension/Replacement Power Supply for LA-140/LT-82 (Australia)*

*01, 02, 03, and 04 designation refers to international plug type (type B, G, C, and I) for the power supply.

Product Overview:

The LA-205 is a replacement for the LT-82 power supply or can be used to power an additional two (2) stationary IR radiators. The power supply connects to the transmitter or the radiators via CAT-5 cabling for simple installation. This unit can be specified for North America, Europe or United Kingdom.

Highlights:

- Standard CAT-5 connection - easy and inexpensive
- Available for multiple countries - can be used in many places around the world
- Cat-5 conversion cable included

Includes:

One (1) LA-205 30 VDC Extension/Replacement Power Supply for LA-140/LT-82

| Product Specification: 30 VDC Extension/Replacement Power Supply for LA-140/LT-82 | |
|---|-------------------------------------|
| Power | |
| Type | In-line switching mode power supply |
| Power Supply Input | 100-240 VAC, 50-60 Hz, 1.5 A |
| Power Output | 30 VDC, 1.5 A, 45 W |
| Power Supply Connector | 5.0mm x 2.1mm Barrel |
| Physical | |
| Cord Length | 85 in. (216 cm) |
| Line Cord Length | 39 in. (99 cm) |
| Color | Dark Grey |
| Shipping Weight | 2.0 lbs (1.1 kg) |
| Weight | 1.1 lbs. (0.5 kg) |

| | |
|-------------------------|--|
| Height | 1.25 in. (3 cm) |
| Width | 2.25 in. (6 cm) |
| Depth | 4.75 in. (12 cm) |
| Environmental | |
| Relative Humidity | 0 to 95% relative humidity, non-condensing |
| Temperature - Storage | -20 °C (-4 °F) to +50 (122 °F) |
| Temperature - Operation | -10 °C (14 °F) to +40 (104 °F) |
| Compliance | |
| Safety | FCC, Industry Canada, CE, RoHS |