

Lumens DC132U document camera is a Full HD/2K professional-quality visualizer which produces bright images and vivid colors. It supports high-resolution capture (QXGA, 1080 HD, and SXGA) with image and video recording up to 30 frames per second. Our no-joint, highly flexible gooseneck enables 360° viewing angles and object viewing from just 4 cm for extreme close-ups. Use the included Ladibug software for advanced image control and connect to remote guests using your favorite conferencing platforms, such as Zoom, Meet, Skype, or Teams. The stylish light weight design makes it easy to carry the DC132U anywhere for creative presentations.



Key Features

- 1080 HD / 2048 QXGA resolution
- USB plug & play
- 16x total zoom (via software)
- Shooting area (18.8" x 14.1") larger than A3
- Macro shooting from 4cm
- 5-year warranty*



2-in-1 Camera Solution

Twist the gooseneck to any angle to view a document, face the presenter or angle towards the class for a live video conference.



Excellent Image Quality

DC132U produces professional-quality images with vivid colors. It outputs 1080p or even 2K video with image and video recording up-to 30 frames per second. The DC132U is ideal for use in education and training.



One-touch Optimization (Auto-Tune)

At the touch of a button, the camera quickly achieves accurate focus, color balance and image exposure.



Imaging Flexibility

The camera can capture documents and objects larger than A3. Adjust the position of the camera for close-up or wide-angle imaging. Zoom into the image using the provided Ladibug software.



Macro Close-Up

Take extreme close-ups (4cm minimum distance) and capture detailed images of small objects such as insects.

Applications



K-12 Education







Corporate

Product Specifications

	Camera		Audio
Sensor	1/3" 3M CMOS	Built-in Microphone	Yes
Total Pixels	3.3MP	Features	
Total Zoom	16x		
Digital Zoom	16x (via Software)	Auto Tune	Yes, One Button for Optimization
Mechanical Zoom	8x		
Output Resolution	2048x1536, 1600x1200,1920x1080, 1280x720, 1024x768, 800x600, 640x480 Video / Audio Recording	Yes (via Software)	
		Image Mode	Photo / Text
Frame Rate	1080p / 720p 30fps	Freeze	Yes
Close-up	4 cm	Mask / Spotlight	Yes (via Software)
Shooting Area Max.	480x360 mm (18.8" x 14.1")	Image Capture	Single or Continuous Capturing (via Software)
Sharpness	MTF 1100 Line	Ladibug™ Software	Support Windows 11, 10, 7
Focus Mode	Auto / Manual		Mac OS X, Chrome OS
Image Rotation	0° / 180° / Flip / Mirror	General	
Lamp	LED Lamp on Camera Head	Anti-Theft	Kensington Anti-Theft Lock Device
Arm	Joint-Free Gooseneck	VESA Mount	Yes, 75mm x 75mm
Input & Output			
Power Supplied	USB Bus Power	Included Accessories	USB 2.0 Cable
Output	USB 2.0	Power Consumption	2.25W (Max.)
Control	USB		Folded : 106 x 280 x 136 mm
USB		Dimonoionos (WyHyD)	(4.2" x 11" x 5.4")
USB Image Transmission	USB 2.0 (480 Mbps)	Dimensions: (WxHxD)	Öpen : 106 x 380 x 350 mm (4.2" x 15" x 13.8")
Driver	UVC / UAC		
USB Video Format	MJPEG	Weight	2.65 lbs (1.2 Kg)

I/O Connections





Lumens Integration, Inc. 4116 Clipper Court Fremont, CA, 94538 Phone: +1-866-600-0988 Fax: +1-510-252-1389 Lumens Europe De Nayerstraat 17 9470 Denderleeuw Belgium Phone : +32-473-58-38-95 Fax : +32-2-452-76-00



Lumens is the registered trademark of Lumens Digital Optics Inc. Changes in specification or design may be done without notification. *The warranty policy may be different depending on the sales region, please contact your local salesperson.