

SPECS DETAILS

Sensor

1 / 2.8" 8.29MP CMOS

Viewing Angle

120° (D) / 107° (H) / 74° (V)

Lens

Fixed lens (F2.2)

Resolution (Max.)

3840 x 2160

Minimum Focus Distance

50 cm

Zoom

8x (Max)

ePTZ

Yes

Auto Framing

Yes

Voice Tracking

Yes

WDR

Yes

2D / 3D Noise Reduction

Yes

Video Format

MJPEG, H.264

Presets

3 for IR remote control

128 for USB command

Mic Element

4 Mics

Pickup Distance

6 Meters

Frequency Response

50 Hz ~ 8kHz

Sensitivity

-32 dBV

SNR

76 dBV

Echo Cancellation

Yes

Noise Suppression

Yes

Configuration

20W, speaker element x1 + passive
diaphragm x 1

Frequency Response

20Hz ~ 20kHz

Speaker Max SPL

95 ± 3dB 0.5m / 5W

Distortion

5% AT 5.0W / 4.47V 1kHz

DC In

Input: 110 ~ 240 VAC, 50 / 60
Hz, 1.0A max.

USB

USB 3.0 type-B, compatible
USB2.0

RJ-45

USB bridge to Ethernet

LED Indicator

Ring, 3 color LED (Green, Blue, Red)

Expansion Mic Input

Yes, with JR-45 connector

Remote Controller

Yes

Kensington

Yes

Mount

TV Mount, Bracket

Weight

3.8 lbs (1.7 kg)

Dimension (W x L x H)

23.51" x 3.55" x 2.95"
(597 x 90 x 75 mm)

Optional Accessory

Expansion Mic: MS-EM1