

# AP-3064

Wi-Fi 6 AX3600 4X4 Dual-Band Indoor Access Point

## **OVERVIEW**

The AP-3064 Wi-Fi 6 Indoor Access Point pairs an upgraded wireless protocol, Wi-Fi 6 (802.11ax), with an easy to navigate user-interface design. Wi-Fi 6 allows for faster speeds, greater network capacity, more device connections, and a greater coverage area than previous access point solutions. The newly added captive portal and walled garden features make it ideal for commercial applications.

The AP-3064 delivers a 2.5 GbE connection to support four dual-band antennas, delivering a high-powered signal to maximize network coverage area. It comes with multiple installation hardware kits designed for easy and precise mounting on walls, drop ceilings, or horizontal surfaces.

## **FEATURES**

#### PERFORMANCE

- High Power 802.11ax Wi-Fi 6 output for maximum coverage
  - Greater device traffic management
  - Better Data Transfer Speeds
  - Lower Latency
  - Broader network coverage
- 4x4 concurrent dual-band wireless
- Concurrent 2.4GHz and 5GHz with beamforming
- VLAN support for creating a secure guest network
- Captive Portal / Walled Garden capable

#### INSTALLATION

- IEEE 802af/at PoE+ power connection
- · Flexible wall mounting plate design for easy precision install
- T-rail mounting clips for installation on drop ceilings
- Free Network Design Service
- Three-year limited warranty
- Free Lifetime Support including US based phone support

## **AP-3064 TECHNICAL SPECIFICATIONS**

HARDWARE FEATURES	DESCRIPTION
Standards Compliance	IEEE 802.11b/g/n/ax, IEEE 802.11a/n/ac/ax, IEEE 802.3af/at
Interface	2.5GbE port with 802.3at Type2, PoE+ Class 4 PD, Also supports 1GbE
Antenna	4 x 2dBi 2.4GHz integrated dual band antenna 4 x 2dBi 5GHz integrated dual band antenna
Button	Reset Button
Power	IEEE 802.3af/at PoE input (Injector not included)
Max Power Consumption	25.5W
Environmental Temperatures	0 °C ~ 40 °C
Dimensions WxHxD in. (mm)	8.86 x 8.86 x 1.69 (225x225x43)
Weight lbs (kg)	2.27 (1.03)
LEDs	One tri-color R/B/G LED









# AP-3064

# **SPECIFICATIONS**

## WIRELESS AND OTHER FEATURES

HARDWARE FEATURES	DESCRIPTION
Frequency	Concurrent 2.4GHz and 5GHz with Beamforming
Wireless Speed	2.4GHz: 1200 Mbps 5GHz: 2400 Mpbs
Wireless Security	WPA2, WPA3, WPA2/WPA3 mixed mode-PSK
Operating Modes	Wireless AP
Other Functions and Features	<ul> <li>Captive Portal Configuration</li> <li>Walled Garden Configuration</li> <li>Target Wake Time (TWT)</li> <li>4x4 Mu-MIMO</li> <li>System Logging</li> <li>Backup &amp; restore configuration</li> </ul>
Certifications	FCC, IC, RoHS, TAA

\* All references to speed are for comparison purposes only. Product specifications, size and shape are

subject to change without notice, and actual product appearance may differ from that depicted herein

# ADDITIONAL INFORMATION

## FREE DESIGN SERVICE

Go to **legrandav.com/cap** to access free design services from Luxul network experts

### **PACKAGE CONTENTS**

- AP-3064 4x4 Dual Band Indoor Access Point
- Mounting Bracket
- Rubber Adhesive Mounted Feet
- Drop Ceiling Mounting Clips
- Quick Install Guide (QIG)
- Regulatory Documentation

## MINIMUM REQUIREMENTS

- Ethernet cable
- Web browser
- PoE+ power source

### WARRANTY & SUPPORT

- Free Lifetime US-Based Support. Phone, Chat, and Email.
- Three-year limited warranty

LEGRAND | AV COMMERCIAL BRANDS C2G | Chief | Da-Lite | Luxul | Middle Atlantic | Vaddio | Wiremold

SIMPLY CONNECTED | legrandav.com

NORTH AMERICA 800.572.2011 & 801.822.5450 av.luxul.support@legrand.com

©2024 Legrand AV Inc. 240306 Rev A 4/24 Luxul is a registered trademark of Legrand AV Inc. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.