MAXHUB UC S07





Ultra Wide Angle, All-in-One Video Soundbar for Huddle & Small Room

MAXHUB UC S07 is a all-in-one Videobar featuring high quality Camera, studio-quality Speaker as well a wide microphone range that satisfies the demand for larger space. A simple all-in-one unified communication solution supports connecting with a laptop, working as a camera, speaker, and microphone.






Ultra HD 4K

Silky smooth Full HD video of up to 30fps



120° FOV

Provides full-room coverage




Auto Framing

Al Vision Intelligent face detection



Voice localization

Speaker Tracking Voice Tracking




Tweeter + Woofer

HI-FI quality Speaker ensures exceptional listening experience



POE

PoE support to simplify installation and minimize cost



USB Plug & Play

Single cable BYOD, autodetect Video, Audio & HDMI



PIR Sensor

Auto on/off the system

UC S07

Camera			
Pixel	12M		
Sensor	1/2.3-inch 12MP Sony sensor.3		
Resolution and Frame Ra	ite		
H.264/MJ	(1)3840× 2160 (4)1280× 720 (7)800× 600 (10)480× 270	(2)2560× 1440 (5)1024× 576 (8)640× 480 (11)352× 288	(3)1920× 1080 (6)960× 540 (9)640× 360 (12)320× 240
YUY2	(1)640× 480 (4)352× 288 (7)160× 120	(2)640× 360 (5)320× 240	(3)480× 270 (6)320× 180
ZOOM		5x digital zoom	
Output Format		MJPG;YUY2;H.264	_
Field Of View		FOV 120° (D)	
Adjustable Angle		± 15° (V)	
Focus Mode		fixed-focus	
Focus Distance		1m	
Special Features	Auto Frame: automatic adjustment FOV to fit in all participants Speaker Tracking: voice triggered people tracking 2 Zooming Pre-sets for instant setting up		

Audio	
Speaker	
Sound Chanel	1.1
Output Power	8W+3W
Maximum Sound Pressure	80dBSPL@1m
Signal to Noise Ratio	>75dB
Frequency Range	150Hz~18kHz
Microphone	
Microphone Quantity	6
Voice Pickup Range	8 m
Microphone Frequency Range	100Hz~7.5kHz
Special Features	Noise Reduction, Echo Cancellation, Anti-Reverberation, Built-in AGC Algorithm
Input/ Output Port	
USB Type-C	USB 3.0
Audio Out	3.5mm
DC 2.0	Power Jack, EITA type DC IN 12V
RJ45	only for PoE,802.3 at

Power	
Power Requirements	12V
Overall Power(Max.)	10W

Compatibility

Support major VC software including ZOOM, Microsoft® Teams, Google Meet, Google Hangouts, Cisco WebEx®, RingCentral, etc.

System Requirements	Supports connecting with a laptop, working as a camera, speaker, and microphone.
---------------------	--

Application Supported MAXHUB Align software for Windows & Mac OS

Auto on/ Auto off **PIR Sensor** When the USB is disconnected and the PIR detects that there is no one for 30 minutes, transfer to sleep mode.

Wall-mounted Mount TV mount kit (Optional)

Physical Specifications	
Dimension(L× H× D)	462× 76× 93 mm(18.2x3.0x3.7 inch)
Dimension(package)(L× H× D)	1pcs 538× 160× 169mm (21.2x 6.3x6.7 inch) 4pcs 628× 433× 380mm (24.7x17.0x15.0 inch)
Maximum Sound Pressure	80dBSPL@1m
Net Weight	1.05Kg/37.04oz
Gross Weight	1pcs TBD 4pcs TBD

Environmental Condition		
Operation Temperature	0°C - 40°C	
Operation Humidity	10% - 90%RH	
Storage Temperature	-20°C - 60°C	
Storage Humidity	10% - 90%RH	
Altitude	Below 5000 meters	

Warranty 3 year hot swap	Accessories one year
--------------------------	----------------------

What's In The Box

1 x USB Cable (1.8m/70.9 inch), 1 x Remote Control (Use with 1 x CR2032 3V battery only), included 1 x Power Adapter, 1 x Wall-mounted Components, 1 x Privacy Cover

