

SPECIFICATIONS

Display Method: STN LCD

Resolution: 320 (W) x 32 (H) Dots

Number of Characters: 20 columns x 2 lines

Character Dot Matrix (Font Resolution): 16 x 16 Dots

Dot Size: 0.35 (W) x 0.6 (H) mm

Viewing Direction: 12 O'clock

Brightness: 400 cd/m²

Character Type: Alphanumeric and Compound (2-Bytes) Words

Character Size: 10 (H) mm x 6 (W) mm

Internal ROM Download Characters: 9 Characters

Viewing Area: 123 (W) x 22.2 (D) mm

Module Kit Dimensions: 139 (W) x 35 (H) x 11.8 (D) mm

Viewing Angle: Max. 90°

Horizontal Rotation: Max. 355°

Weight (Module Kit Only): Approx. 70 grams

Commands Mode: Ultimate (Epson command compatible), LD540, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL

Language Support: [Compound (2-Bytes) Words]

Traditional Chinese, Simplified Chinese, Korean, Arabic, Persian

[Alphanumeric]

US English, Int'l English, Turkish, Bosnia, Croatian, Czech, Danish, Dutch, Estonian, Faroese, Finnish, Flemish, French, Fr Canadian, German, Greek, Hebrew, Hungarian, Icelandic, Indonesian, Irish, Italian, Katakana, Latvian, Lithuanian, Norwegian, Polish, Portuguese, Romanian, Russian, Slovene, Slovak, Spanish, Swedish...

Interface: RS-232 (serial) / USB in 5V only

Connection | Baud Rate: Direct connection 9600 or 19,200 bps

Reliability | MTBF: 30,000 hours

Power Consumption: 5~12 VDC

Agency Approvals: FCC, CE

Weight (net): 0.168 kg

Housing Color: Silver

What's Included: 2x20 LCM