



FORWARD PRE-CONFIGURED BGR - 45RU, 32"D

BGR-4532-FWD |

FEATURES & BENEFITS

An AV foundation built for tomorrow's speed. The Forward accessories and options included with the Forward Pre-Configured BGR were hand selected by our product experts with crucial input from customers. The result, a single part number aimed at helping you get the job done in a fraction of the time with everything needed for an optimized foundation to deliver the ultimate AV experience.



The Forward Pre-Configured BGR Includes:

Power:

- Forward UPS Caster Base ([FWD-CBS-2KVA-BGR32](#)) with a [UPS-2200R](#) pre-installed from our factory ready to be integrated
- (1) 16 outlet Select Series Vertical PDU with RackLink™ ([RLNK-1615V](#))

FoPanels:

- (4) Forward 1RU flanged blank panels ([FWD-EB1](#)) and (2) Forward 2RU flanged blank panels ([FWD-EB2](#)) blank panels for 5X faster installation with no rackscrews

Horizontal Cable Management:

- (1) 4pk of Forward straight horizontal lacer bar ([FWD-LB-1A-4PK](#)) and (1) 4pk of Forward 2" offset horizontal lacer bar ([FWD-LB-2A-4PK](#)) for 5X faster installation with no rackscrews

Vertical Cable Management:

- (1) 45RU Forward Vertical Wire Grid Lace for vertical and horizontal cable routing on a single lace bar ([FWD-LACE-WB3-44-45](#))
- (1) Forward Vertical Cable Management Lace ([FWD-LACE-UMV-44-45](#)) with the patented universal hole pattern. Compliment with [FWD-C-RING](#), [FWD-D-RING](#) and [FWD-TSW-15](#)
- (2) Lever Lock™ vertical channel ([LL-VC21](#))

Cable Management Accessories:

- (1) 15pk of Forward tie saddles for optimal cable management in any direction using absolutely no hardware. Accepts both cable zip ties and hook & loop. ([FWD-TSW-15](#))
 - (2) Velcro® straps for tie saddles ([TW12](#))
 - Small Device Mounting:**
 - (2) 4pk of Forward small device clamps for quick mounting of small, non-rackmount devices without any hardware ([FWD-SIDECLMP-4](#))
 - (1) Lever Lock™ plate for small device mounting ([LL-VP2110](#))
 - Lighting:**
 - (1) 45RU Forward utility light (pair) with IR sensor and dimmer ([FWD-LT-UTL-44-45-D](#))
 - Thermal Management:**
 - (1) DC fan top with 4 fans moving 276CFM. Includes controller ([BGR-276FT-FC](#))
 - Options:**
 - (1) Solid front door ([BFD-45](#))
 - (1) Pair of side panels ([BSPN-45-32](#))
 - (1) set of leveling feet ([LF-HD](#))
 - Hardware:**
 - (100) 10-32 threaded rackscrews ([HP](#))
-

SPECIFICATIONS

GENERAL INFO

Gangable: Yes
 Available Colors: Black
 Finish: Black Powder Coat
 Input Plug Type: NEMA 5-20P (UPS), NEMA 5-15P (Power Strip)

ASSEMBLY/INSTALLATION INFORMATION

Assembly Required: Yes

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

OSHPD: Yes - OPM
 RoHS: Yes
 Greenguard: Yes

DIMENSIONS

Usable Depth: 22.8
 Usable Height: 78.875
 Usable Width: 21
 CFM: 276
 Panel Width: 19
 Capacity Weight (Metric): 4708288801
 Capacity Weight (US): 1038
 Depth (Metric): 855.73
 Depth (US): 33.69
 Height (Metric): 2300.48
 Height (US): 90.57
 Width (Metric): 584.20
 Width (US): 23
 Primary Packaging Weight (Metric): 0
 Product Weight (Metric): 1496854821
 Product Weight (US): 330
 Rack Units: 45

CORD INFORMATION

Cord Length Metric: 228,6
Cord Length US: 9

TECHNICAL INFORMATION

Rackrail Type: Forward Rackrail
Seismic Load Capacity: N/A
AC Voltage Output: 120V
Amps: 20A
Material: Steel