



## DISPLAYSTATION SERIES, CART WITH CASTERS

DS-1000SC-AL. |

### FEATURES & BENEFITS

We recognize that there is a lot of crossover between the Middle Atlantic and Chief product lines, spanning a few categories. With this in mind, Middle Atlantic will begin to phase out these display mounts and AV storage solutions this year. Middle Atlantic's goal is to make this process as seamless as possible to our partners. If you have further questions, concerns or needs, please contact 973-839-1011.



- Ships with an integrated power strip
- Designed for professionally-finished installations with a convenient cable management system and power strip incorporated into the support channel
- UL Listed to the highest standard for safety in multi-use environments including public, educational and institutional spaces
- Portrait to landscape adjustability of screen orientation with display mounted (single post models only)
- Competitively-priced
- Mounts single displays up to 100" (VESA 1000 models)
- Includes hex bits for faster assembly
- Attractive aluminum finish

### SPECIFICATIONS

DisplayStation Series Display carts and stands shall be Middle Atlantic Products model #DS-\_\_\_-AL (see chart for available models). Overall dimensions of DS shall be \_\_\_"H x \_\_\_" W x \_\_\_"D (see drawing). DS shall have\_\_\_ (Plate, Levelers, Casters (2 locking), refer to chart) base. DS shall accept 1 monitor, with a maximum VESA pattern of (600x400, 1000x600) and accept displays with a recommended diagonal measurement of (37" to 70", 60" to 100"), refer to chart. DS Series single post model shall have portrait to landscape screen adjustability (refer to drawing.) DS series shall have a clear anodized aluminum finish. DS shall have an overall weight capacity of (150, 185) lbs, with no more than (125, 175) lbs. for the monitor, refer to chart. DS shall include a 15 Amp power strip with 4 outlets and 12' cord with 5-15P termination. DS shall have integrated cable management. DS shall be UL Listed for institutional use to UL 1678 in the US and CAN/CSA C22.2 No. 60065-03 in Canada.. DS shall comply with requirements of RoHS EU Directive 2002 / 95 / EC and 2011/65/EU. DS shall be manufactured by an ISO 9001 registered company. DS shall be warranted to be free from defects in material or workmanship under normal use and conditions for 7 years.

### GENERAL INFO

Finish: Aluminum  
UL Standards Tested: Yes

#### **LISTING AGENCIES/THIRD PARTY CERTIFICATIONS**

RoHS: Yes  
UL Listing No: UL 1678

#### **DIMENSIONS**

Capacity Weight (US): 185  
Depth (US): 41.23  
Height (US): 67.81  
Width (US): 57.12

#### **CORD INFORMATION**

Cord Length US: 12

#### **TECHNICAL INFORMATION**

Monitor Mounting: Yes  
Number Of Outlets: 4