



CONVENIENT DRYING OPTIONS

7.0 Cu. Ft Tumble Dryer

MLTE41N1BWW 7.0 Cu. Ft Electric Dryer

MLTG41N1BWW 7.0 Cu. Ft Gas Dryer

Our versatile, 7.0 Cu. Ft. Dryer has up to 8 pre-set cycles and 4 temperature settings along with a convenient sensor dry feature. The reversible door can be adjusted to open from the left or right for maximum placement versatility. An end-of-cycle signal tells you when your laundry is dry.

Large, 7.0 Cu. Ft. Capacity

Dry everything at once including king-size comforters, towels and linens with the extra-large drum.

Sensor Dry

Drying is automatically paused when the clothes reach the ideal dryness, preventing damage from over-drying while saving energy.

End-of-cycle Signal

A signal tells you when your laundry is damp dry or completely dry depending on your setting.

Sanitize Cycle

Longer drying time ensures most of the germs and bacteria are removed, providing stronger and significant sanitization and anti-allergy effect.

No More Wrinkles

After the drying cycle is finished, the drum will constantly rotate at a low frequency to prevent wrinkles caused by piling, and cold air will be blown into the drum to keep clothes fresh.

7.0 Cu. Ft Tumble Dryer

Models MLTE41N1BWW, MLTG41N1BWW



SPECIFICATIONS

Models		MLTE41N1BWW	MLTG41N1BWW
Fuel Type		Electric	Gas
UPC			
PERFORMANCE			
ENERGY STAR®		-	-
FEATURES			
Capacity (cu. ft.)		7.0	7.0
No. of Cycles	Total	8	8
	Sensor Dry	Normal, Bedding, Heavy Duty, Delicates, Quick Dry	Normal, Bedding, Heavy Duty, Delicates, Quick Dry
	Manual Dry	20 min, 50 min, 80 min	20 min, 50 min, 80 min
Sensor Dry		Yes	Yes
No. of Dryness Level Selections		4 (Damp, Less, Normal, More)	4 (Damp, Less, Normal, More)
No. of Temperature Selections		4 (No Heat, Low, Medium, High)	4 (No Heat, Low, Medium, High)
Interior Light(s)		-	-
Lint Filter		Yes	Yes
Lint Filter Indicator Light		-	-
My Cycle		-	-
Steam Function		-	-
Reversible Door		Yes	Yes
3-Way Venting		Yes	Yes
Exhaust Vent Location		Rear, Bottom, & Left	Rear, Bottom, & Left
End-Of-Cycle Signal		Yes	Yes
ELECTRICAL			
Voltage (V)		120/240	120
Amperage (A)		24	11
UL Rated		Yes	Yes
Power Cord Included		-	-
PHYSICAL ATTRIBUTES			
Tub/Drum Material		Aluminum Plate	Aluminum Plate
Cabinet		Painted Steel	Painted Steel
Double Layer Drying Rack		-	-
Control Panel / Color		Dial / Gray	Dial / Gray
Door / Trim		Painted Steel / White	Painted Steel / White
Color		White	White
Dimensions (W*D*H)	in	27 x 30 x 41-4/5	27 x 30 x 41-4/5
Net Weight		127.9 lbs	127.9 lbs
Warranty		Parts & Labor, 1 Year	Parts & Labor, 1 Year