

NEC AccuSync™ Series

17"-24" LCD monitors ideal for value-conscious users

High-quality LCD monitors don't necessarily have to be associated with high-end price tags.

NEC AccuSync Series monitors have set a new standard in value for the flat-panel monitor category, offering you a perfect opportunity to take advantage of the many benefits offered by the latest display technology without having to break your budget. The 17" NEC AccuSync **AS172**, 19" **AS193i** and widescreen 22" **AS221F** and 24" **AS241F** deliver eco-friendly, value-driven and cost-conscious display solutions to small-to-medium-sized businesses and home office users. The widescreen models increase productivity by expanding your working area to simultaneously view multiple application windows.

It's easy to be green.

The AccuSync Series is loaded with features that promote environmental consciousness. Eco-friendly benefits include ECO Mode™ and an off timer for further energy savings, a resettable carbon footprint meter for tracking the conservation of green gas emissions, and a significant reduction in packaging materials. The AccuSync Series sets the bar for "green" technology by using LED backlighting, which is more energy-efficient. Compared to their predecessors, these model consume up to 33% less power overall, weigh up to 20% less, radiate less heat, use less packaging, utilize recycled plastics in their production and are free of hazardous materials such as mercury, lead and arsenic.



Highlights

- LED backlight technology provides for industry-leading low power consumption and less hazardous materials
- Ambix® dual-input technology allows for digital/analog compatibility
- Tilt adjustable stand helps you reach a more comfortable view
- Integrated multimedia speakers provide an option for business conferencing
- IPS LCD for outstanding color and wide-angle viewing (AS193i, AS221F, AS241F)
- ECO Mode (default setting) sets the brightness variable from 0-80%, saving more power and reducing your energy costs
- Carbon footprint meter helps track and calculate the reduction of green gas emissions
- Rapid Response™ technology delivers virtually uninterrupted, undistorted viewing of high-speed, full-motion video
- ENERGY STAR® and TCO qualifications reduce electrical costs and lower total cost of ownership

Model		AS172-BK	AS193i-BK	AS221F	AS241F	
DISPLAY	Panel Technology	TN	IPS	IPS	IPS	
	Backlight Type	LED	LED	LED	LED	
	Viewable Image Size	17"	19"	21.5"	23.8"	
	Aspect Ratio	5:4		16:9		
	Native Resolution	1280 x 1024		1920 x 1080		
	Pixel Pitch	0.26mm	0.29mm	0.248mm	0.275mm	
	Pixels Per Inch (at native resolution)	96	86	102	93	
	Brightness (typical)	250cd/m ²				
	Contrast Ratio (typical)	1000:1				
	Viewing Angle (typical)	170° Vert., 170° Hor. (85U/85D/85L/85R) @ CR>10				
	Response Time (typical)	5ms	14ms	6ms		
	Displayable Colors	More than 16.7 million				
	Horizontal (Analog/Digital)	31.5-81.1 KHz				
	Vertical	56-76 Hz				
	Input Signal	Video	Analog RGB 0.7 Vp-p/75 Ohms			
Sync		Separate Sync: TTL Level (Positive/Negative)				
Input Connectors	DVI-D, VGA 15-pin D-sub		DisplayPort, HDMI, VGA 15-pin D-sub, Stereo Mini Jack			
"POWER CONSUMPTION"	On (typical)	11W	18W	13W		
	Power Savings Mode (typical)	0.15W		0.27W		
PHYSICAL SPECIFICATIONS	Dimensions (WxHxD)	With stand	14.7 x 14.7 x 8.1 in. / 373.2 x 373.1 x 205.1mm	16.2 x 15.9 x 8.1 in. / 412.5 x 403.1 x 205.1mm	19.2 x 14.9 x 7.2 in. / 487.5 x 379.4 x 182.0 mm	21.2 x 16.1 x 7.2 in. / 538.1 x 408.0 x 182.0 mm
		Without stand	14.7 x 12.2 x 2.7 in. / 373.2 x 310.2 x 69mm	16.2 x 13.4 x 2.7 in. / 412.5 x 341.2 x 69mm	19.2 x 11.5 x 1.8 in. / 487.5 x 291.7 x 46.8 mm	21.2 x 12.6 x 1.8 in. / 538.1 x 320.2 x 46.8 mm
	Net Weight	With stand	7.3 lbs. / 3.3 kg	8.6 lbs. / 3.9 kg	6.8 lbs. / 3.1 kg	7.7 lbs. / 3.5 kg
		Without stand	6.4 lbs. / 2.9 kg	7.7 lbs. / 3.5 kg	6.0 lbs. / 2.7 kg	6.8 lbs. / 3.1 kg
	VESA Hole Configuration	100 x 100mm				
"ENVIRONMENTAL CONDITIONS"	Operating Temperature	41-95°F / 5-35°C				
	Operating Humidity	20-80%				
	Operating Altitude	6562 ft. / 2000m		16404 ft. / 5000m		
	Storage Temperature	14-140°F / -10-60°C				
	Storage Humidity	10-85%				
	Storage Altitude	40,000 ft. / 12,192m				
ENVIRONMENTAL COMPLIANCE	ENERGY STAR			8	8	
	TCO	6		8		
	RoHS	Yes				
ADDITIONAL FEATURES	ECO Mode; Carbon footprint meter; Thin frame; Tilt; Rapid Response; Ambix; XtraView; OSD user controls; NaViSet software; Cable management; VESA mount; HDCP; DDC/CI; No Touch Auto Adjust; Plug and Play (VESA DDC 2B); VESA DPMS power management; AccuColor colorcontrol; Digital smoothing; Digital controls; ISO 9241-307 Class I					
SHIPS WITH	Setup sheet; User manual; Power cord; 15-pin D-sub cable	Setup sheet; User manual; Power cord; Video cable; Remote if applicable	Power cord DisplayPort cable			
LIMITED WARRANTY	3 years	3 years	3 years	3 years		

* Warranty restrictions apply. Contact your representative for details.

Ambix is a registered trademark and AccuSync, ECO Mode, NaViSet and Rapid Response are trademarks of NEC Display Solutions. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change.

©2019 NEC Display Solutions of America, Inc. and the NEC logo are registered trademarks of NEC.