

Ultra narrow bezel desktop displays  
designed for everyday business use

# NEC MultiSync® Series Narrow Bezel

Ultra Narrow 22" | 24" | 27"



# Tiny bezels, large value.

NEC's ultra narrow bezel MultiSync® E Series deliver all of the business-class features needed with none of the bezels. The MultiSync® E221N, E241N and E271N include future-proof connectivity and environmentally friendly benefits in a package with ultra narrow bezels and a slim design.



E Series Desktops	
22"	E221N
24"	E241N
27"	E271N

## Highlights

- Small bezels on three sides (1mm each)
- Touch on screen menu controls easy navigation, making display adjustments easier than ever
- 4 way ergonomic stand includes pivot in both directions
- TuV Certified for Flicker Free and Low Blue Light

E221



E241N






## MultiSync® E Series Ultra Narrow Features

### Ultra Thin Design

The MultiSync® E Series Ultra Narrow displays feature some of the industry's smallest bezels at 1.0mm on each side. In addition, the slim cabinet is only 43.2mm from the front of the panel to the VESA mounting plate and the panel portion of the monitor is a thin 18.1mm.



### Comprehensive Input Panel

DisplayPort, HDMI, and 15-pin VGA connect you to the latest peripherals and future-proofs your investment.



### Adjustable for Every Workspace

Four-way ergonomic stand boasts dual direction pivot, tilt, swivel and height adjustment up to 110mm to maximize your viewing comfort.




### IT-Friendly Features

The optional NaViSet™ Administrator 2.0 software offers an intuitive graphical interface, allowing for easy adjustment of display settings via mouse and keyboard. NaViSet Administrator provides all the advanced control to remotely located IT professionals.

The included thin / zero client mount makes installing a thin client easy. The 100mm VESA mount is designed to fit most thin clients on the market.





MultiSync® MODEL		E221N	E241N	E271N	
<b>Display</b>	Panel Technology	AH-IPS			
	Backlight Type	White LED			
	Viewable Image Size	21.5"	23.8"	27"	
	Aspect Ratio	16:9			
	Native Resolution	1920x1080			
	Pixel Pitch	0.24795 mm	0.2745 mm	0.27mm	
	Pixels Per Inch	102.4 PPI	92.6 PPI	82 PPI	
	Brightness (typical)	250 cd/m <sup>2</sup>			
	Contrast Ratio (typical)	1000:1			
	Viewing Angle (typical)	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10			
	Response Time (typical)	6ms			
	Displayable Colors	16.8 million			
	Synchronization Range				
	Horizontal (Analog/Digital)	31.5 KHz - 81.1 KHz			
	Vertical	56.0Hz - 75.0 Hz			
	Input Signal	Video	Analog RGB 0.7 Vp-p/75 Ohms		
Sync		Separate sync: TTL Level (Positive/Negative)			
Input Connectors	DisplayPort 1.1a, HDMI 1.4, VGA, analog audio				
Output Connectors	Headphone audio				
<b>POWER CONSUMPTION</b>	On (typical)	25W	28W	16W	
	Power Savings Mode (typical)	0.29W			
<b>PHYSICAL SPECIFICATIONS</b>	Dimensions (WxHxD)	With stand	488.1 x 359.8 - 469.8 x 213.9 mm / 19.2 x 14.2 - 18.5 x 8.4 in.	538.6 x 373.9 - 483.9 x 213.9 mm / 21.2 x 14.7 - 19.1 x 8.4 in.	24.0 x 14.8 - 20.0 x 11.1 in. / 610.4 x 376.9 - 503.9 x 282.6 mm
		Without stand	488.1 x 291.0 x 47.6 mm / 19.2 x 11.5 in. x 1.9 in.	538.6 x 319.4 x 47.6 mm / 21.2 x 12.6 x 1.9 in.	24.0 x 14.2 x 1.8 in. / 610.4 x 359.9 x 46.6 mm
	Net Weight (with stand)	5.0 kg / 11.0 lbs.	5.5 kg / 12.1 lbs.	18.1 lbs. / 8.2 kg	
	Net Weight (without stand)	3.0 kg / 6.6 lbs.	3.5 kg / 7.7 lbs.	11.2 lbs. / 5.1 kg	
	VESA Hole Configuration	100mm x 100mm			
	Height Adjust	110mm		130mm	
<b>ENVIRONMENTAL CONDITIONS</b>	Operating Temperature	5°C - 35°C / 41°F - 95°F			
	Operating Humidity	20% - 80%			
	Operating Altitude	2000 m / 6562 ft			
	Storage Temperature	-10°C - 60°C / 14°F - 140°F			
	Storage Humidity	10% - 85% (without condensation)			
	Storage Altitude	40,000 ft. / 12,192m			
<b>ENVIRONMENTAL COMPLIANCE</b>	ENERGY STAR	7.0			
	TCO	7.0			
	RoHS	Yes			
<b>LIMITED WARRANTY</b>	3 years				
<b>ADDITIONAL FEATURES</b>	ECO Mode; Carbon footprint meter; Ultra Narrow Bezels; Tilt; Swivel; Dual Direction Pivot; Carrying handle; Audio input; Headphone output; Rapid Response; Ambix; XtraView; OSD® user controls; OSD Lock Out; Cable management; NaViSet™ Administrator 2; VESA mount; HDMI-capable via DVI adapter; HDCP; DDC/CI; No Touch Auto Adjust; Plug and Play (VESA DDC 2B); VESA DPMS power management; Dynamic Video Mode; Digital controls; ISO 9241-307 Class I				
<b>SHIPS WITH</b>	Setup Manual, Contents Sheet, NaViSet Administrator 2 flyer, Power cord, DisplayPort cable, Thin / Zero client VESA plate				



MultiSync® is a registered trademarks and ECO Mode and ControlSync are Trademarks of NEC Display Solutions. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change.

©2018 NEC Display Solutions of America, Inc. and the NEC logo are registered trademarks of NEC.