# **Product Specifications**

## Display

Panel Technology	Direct View LED Aspect Ratio		
Native Resolution	480x270	Module Resolution	
Pixel Configuration	Flip Chip COB	Pixel Pitch	
<b>Brightness</b> (typical)	800 cd/m <sup>2</sup> Brightness (maximur		
Contrast Ratio (typical)	20000:1 Viewing Angle (typ		
Refresh Rate	Up to 3840 Hz	Active Screen Area	
Orientation	Landscape	Dimming Capability	
<b>Color Processing</b>	Up to 16 bit	Displayable Colors	
Color Temperature (Max) (°K)	3000 Color Temperature		
Color Temperature (Min) (°K)	9500 Gamma (Max)		
Gamma (Typical)	2.8 Gamma (Min)		
Lifetime	100,000 hours		

# **Signal Compatibility/Connectivity**

#### **Input Terminals**

Digital:

1x 1000BaseT RJ-45

External Control:

RS232 / USB

#### **Power Consumption (typical)**

2560Watts	Power Consumption (max)
1664 Watts	
	Weight
	Net Weight (without stand):
48.5 mm	15.4 lbs. / 7 kg.
	Servicability:
	Front Service
	IP Level:
	IP40
	Certifications:
	1664 Watts

- CCC
- CE
- ETL
- FCC Class A

#### **Environmental Conditions**

<b>Operating Temperature</b>	-4° to $104$ °F / -20° to $40$ °C	<b>Operating Humidity</b>
Storage Temperature	-4° to $113$ °F / -20° to $45$ °C	<b>Storage Humidity</b>
Environment	Indoor	
Limited Warranty (parts & labor)		

3 years

## Accessories

Included	•	LED Controller	Optional
	•	LED Modules (64 Cabinets, 512	
		Pixel Cards)	
	•	Overframe Kit (8x8)	
	•	Pixel Card Removal Tool	
	•	Power Bar; Spare Parts Kit	
	•	Wall mount (8x8)	