

|  |   |
|--|---|
| <b>PHYSICAL</b>                          |   |
| <b>Gross Dimensions</b>                  | 56.3 x 36.2 x 9.8 in. / 1430.0 x 920.0 x 250.0mm                |
| <b>Gross Weight</b>                      | 80.5 lbs. / 36.5kg  |
| <b>Net Dimensions (w/o stand; WxHxD)</b> | 48.8 x 28.1 x 2.4 in. / 1239.6 x 713.0 x 61.1mm                 |
| <b>Net Weight (w/out stand)</b>          | 58.2 lbs. / 26.4kg  |
| <b>Bezel</b>                             | 0.49in./0.47in., 0.61in./0.49in. ; 12.5mm/12.0mm, 12.0mm/15.6mm |
| <b>VESA Hole Configuration</b>           | 300 x 300mm (M6 x 4-hole)                                       |
| <b>COUNTRY OF ORIGIN</b>                 |   |
| <b>Country of Origin</b>                 | China   |
| <b>GREEN COMPLIANCE</b>                  |   |
| <b>Energy Star Compliance</b>            | Yes, Energy Star 8.0  |
| <b>UL/C-UL</b>                           | Yes   |
| <b>RoHS</b>                              | Yes   |
| <b>TAA Compliant</b>                     | No  |
| <b>FEATURES</b>                          |   |

|   |   |
|---|---|
| <b>Viewable Image Size (Diagonal)</b>   | 54.6"   |
| <b>Cabinet Color</b>                    | Black   |
| <b>Panel Technology</b>                 | VA  |
| <b>Native Resolution</b>                | 3840 x 2160   |
| <b>Haze %</b>                           | 25  |
| <b>Viewing Angle</b>                    | 89°/89°/89°/89°   |
| <b>Pixel Pitch</b>                      | 0.315   |
| <b>Brightness (typical)</b>             | 500 cd/m2   |
| <b>Contrast Ratio (typical/Dynamic)</b> | ≥8,000:1 (Out of the box conditions, local dimming ON)    |
| <b>Response Time</b>                    | 8ms   |
| <b>Active Screen Area (W x H)</b>       | 47.6 x 26.8 in. / 1209.6 x 680.4mm                        |
| <b>Aspect Ratio</b>                     | 16:9  |
| <b>Displayable Colors</b>               | 1.07 billion  |
| <b>CONNECTIVITY-Inputs</b>              |   |
| <b>Digital</b>                          | HDMI (2.0 x 2 with HDCP 2.2), DisplayPort (1.2 with HDCP) |
| <b>Analog</b>                           | None  |

|                                    |   |
|------------------------------------|---|
| <b>Audio</b>                       | DisplayPort Audio x1, HDMI Audio x2               |
| <b>External Control</b>            | RS-232C, LAN (100Mb), 3.5mm Mini-Jack (IR Remote) |
| <b>Input Data</b>                  | USB 2.0 (Media Player, 5V/2A Power)               |
| <b>CONNECTIVITY-Outputs</b>        |   |
| <b>Digital</b>                     | N/A   |
| <b>Analog</b>                      | N/A   |
| <b>Audio</b>                       | Audio Mini-Jack Out (Fixed/Variable)              |
| <b>External Control</b>            | N/A   |
| <b>Audio Amplifier</b>             | N/A   |
| <b>Advanced Feature Set</b>        |   |
| <b>Protective/Touch Panel</b>      | No  |
| <b>Advanced Thermal Protection</b> | Yes   |
| <b>Panel Grade</b>                 | Professional                                      |
| <b>Tile Matrix</b>                 | Yes 10x10   |
| <b>TileComp Bezel Compensation</b> | Yes   |

|  |   |
|--|---|
| <b>Color Temperature Adjustment for color matching</b> | Yes   |
| <b>Inactive border area</b>                            | 0.55in./0.55in., 0.55in./0.55in. ; 13.9mm/13.9mm, 13.9mm/13.9mm |
| <b>Ethernet control</b>                                | Yes   |
| <b>RS-232C control</b>                                 | Yes   |
| <b>Raspberry Pi Support</b>                            | Yes   |
| <b>Media Player</b>                                    | Integrated  |
| <b>Expansion Slot</b>                                  | Yes, SDM-S or SDM-L   |
| <b>Portrait Capability</b>                             | Yes   |
| <b>Power Management</b>                                | Yes   |

|   |   |
|---|---|
|   | <p><b>Other</b> AMX Support, Automated Email Alert Function, CEC Support through HDMI, Crestron Roomview Support, Display Browser Control, Display Wall Calibrator Compatible, HDR Support (PQ, HLG, HDR10), Key Guide, NaViSet Administrator 2 Compatible, OSD Rotation for Portrait Orientation, Accepts Intel(R) SDM-S or SDM-L, PJ Link Support, Power USB Port (5V/2A), Raspberry Pi Compute Module 4 Compatible, Removeable Logo Ornament, Real Time Clock, Local Dimming, TileMatrix, Cisco Webex Compatible, SNMP, Consumer Electronics Control (CEC), Carrying Handles, Integrated USB Media Player, Integrated Temperature Sensors and Cooling Fans, Joystick Controls on display, Full Input Detect Functionality, Programmable Gamma, Energy Star 8.0, Scheduler Function, Off Timer, Vacation Switch</p> |
| <b>POWER</b>                            |   |
| <b>Power Requirements</b>               | 2.9A @ 100V, 1.1A @ 240V  |
| <b>Power Consumption (Typical)</b>      | 120W  |
| <b>Power Consumption (Standby Mode)</b> | <0.5W   |
| <b>Environmental Conditions</b>         |   |

|                              |   |
|------------------------------|---|
| <b>Operating Temperature</b> | +5°C ~ +40°C / 41°F ~ 104°F   |
| <b>Operating Humidity</b>    | 20% ~ 80% (without condensation)  |
| <b>ACCESSORIES</b>           |   |
| <b>Included</b>              | 3m AC Power Cord, 2.0m DisplayPort Cable, 2.0m HDMI Cable, IR Remote Control, Batteries, Setup Manual, Clamps |
| <b>NEC Options</b>           | Table Top Stand (ST-43M)  |