

# Product Specifications

## Display

<b>Panel Technology</b>	Direct View LED	<b>Aspect Ratio</b>
<b>Native Resolution</b>	640x360	<b>Module Resolution</b>
<b>Pixel Configuration</b>	4 in 1 IMD	<b>Pixel Pitch</b>
<b>Brightness (typical)</b>	600 cd/m <sup>2</sup>	<b>Brightness (maximum)</b>
<b>Contrast Ratio (typical)</b>	5000:1	<b>Viewing Angle (typical)</b>
<b>Refresh Rate</b>	Up to 3840 Hz	<b>Active Screen Area</b>
<b>Orientation</b>	Landscape	<b>Dimming Capability</b>
<b>Color Processing</b>	Up to 16 bit	<b>Displayable Colors</b>
<b>Color Temperature (Max) (°K)</b>	3000	<b>Color Temperature (Typical)</b>
<b>Color Temperature (Min) (°K)</b>	9500	<b>Gamma (Max)</b>
<b>Gamma (Typical)</b>	2.8	<b>Gamma (Min)</b>
<b>Lifetime</b>	100,000 hours	

## Signal Compatibility/Connectivity

<b>External Control</b>	RS232 / USB	<b>Input Terminals</b> Digital: 1x 1000BaseT RJ-45 External Control: RS232 / USB
-------------------------	-------------	--

## Power Consumption (typical)

<b>On</b>	960Watts	<b>Power Consumption (max)</b>
-----------	----------	--------------------------------

## Physical Specifications

<b>Dimensions (WxHxD)</b> Without stand: 97.3 x 42 x 3.2 in. / 2472 x 1066 x 82 mm	<b>Weight</b> Net Weight (without stand): 232.8 lbs. / 105.6 kg. Servicability: Front Service IP Level: IP20 Certifications: <ul style="list-style-type: none"><li>• CCC</li><li>• CE</li><li>• ETL</li><li>• FCC Class A</li><li>• RoHS</li></ul>
--	---

## Environmental Conditions

<b>Operating Temperature</b>	-4° to 104°F / -20° to 40°C	<b>Operating Humidity</b>
<b>Storage Temperature</b>	-4° to 113°F / -20° to 45°C	<b>Storage Humidity</b>
<b>Environment</b>	Indoor	
<b>Limited Warranty (parts &amp; labor)</b>		

3 years

## Accessories

<b>Included</b>	See NEC Representative for accessories	<b>Optional</b>
-----------------	--	-----------------