

# Product Specifications

## Display

<b>Aspect Ratio</b>	4x3	<b>Native Resolution</b>
<b>Maximum Resolution</b>	Up to 4K@30Hz (3840x2160) with Advanced AccuBlend, Pixel clock frequency:less than 300MHz	<b>Contrast Ratio (typical)</b>

## Synchronization Range

<b>Horizontal (Analog/Digital)</b>	15-100kHz (RGB: 24kHz or over)	<b>Vertical</b>
------------------------------------	--------------------------------	-----------------

## Signal Compatibility/Connectivity

<b>Supported Video Standards</b>	NTSC3.58/NTSC4.43/PAL/PAL-N/PAL-M/PAL-60/SECAM	<b>SD/HD Video Signal Comp</b>
----------------------------------	--	--------------------------------

<b>PC Signal Compatibility</b>	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA	<b>Macintosh Signal Compati</b>
--------------------------------	--	---------------------------------

<b>External Control</b>	RS-232 (D-Sub 9pin), IR, LAN	<b>Input Terminals</b> RGB1(analog): VGA 15pin D-sub RGB2(digital): HDMI w/ HDCP RGB3(digital): HDMI w/ HDCP Video 1: RCA Audio 1: Stereo Mini Jack Audio 2: RCA (L/R)
-------------------------	------------------------------	--

## Output Terminals

Audio:  
Stereo Mini Jack  
Audio Out:  
Yes (variable)

## Power Consumption (typical)

<b>On</b>	267W	<b>Input Current</b>
<b>Power Requirements</b>	100-240V AC, 50/60 Hz	

## Physical Specifications

<b>Dimensions (WxHxD)</b>		<b>Weight</b>
Product: 13.6 x 10.3 x 4.1 in. (345 x 261 x 104.6 mm)		Net Weight: 7.1 lbs. (3.2 kg)

Shipping:  
17.7 x 15.4 x 7.8 in. (450 x 390 x 200 mm)

Shipping:  
10.4 lbs. (4.7 kg)

### Environmental Conditions

**Operating Temperature** 41-104°F / 5-40°C

**Storage**

### Limited Warranty (parts & labor)

1 Year

### Additional Features

- Keystone correction
- Wireless LAN (Optional)
- USB Viewer
- Cornerstone
- Auto power on
- ECO Mode technology
- Variable audio out
- Carbon savings meter
- Virtual Remote
- Sleep timer
- Built-in wall color correction
- Advanced AccuBlend
- AutoSense

MultiPresenter

- 

### Optical

<b>Display Technology</b>	0.63" LCD	<b>Lamp Type</b>
<b>Light Output(Lumens)</b>	3700 normal	<b>Light Source Life</b>
<b>Screen Size (diagonal)</b>	30 - 300 in. / 0.76 - 7.62m	<b>Throw Ratio</b>
<b>Projection Distance</b>	2.9 - 35.9 ft. / 0.9 - 10.9 m	<b>Projector Angle</b>
<b>Lens</b>		<b>Keystone Correction</b>
Zoom:		
1.2		
Focus:		
Manual		
F number, fnumber:		
F:1.6~1.76 /f=19.158~23.018mm		

### Mechanical

**Installation Orientation** Floor/Front, Floor/Rear, Ceiling/Front, Ceiling/Rear **Fan Noise**

---

**Regulations**

USA: UL (UL60950-1/UL62368-1) FCC  
Part15 Class B, Canada: C-UL  
(CSA60950-1) ICES-003 Class B, NOM