## newline



## **STREAMLINE** YOUR SUCCESS

The NT+ Series is a non-touch display that brings your presentations to life in vivid Ultra-High Definition (4K) resolution. Focus on just the tools you need to succeed in your organization without paying more for features you won't use.

Wirelessly cast to the screen from any mobile device, tablet, desktop, or laptop. Whether you use Windows, Mac, or Chrome, the NT Series lets you share your screen through a wireless connection or through the multiple I/O ports built into the panel. Access your files on your preferred Cloud storage system right on the display. The built-in file viewer lets you easily navigate through local files, Cloud storage, and files from connected USB thumb drives.

Rediscover the simplicity of real innovation with the new NT+ Series.

Newline NT+ Series includes the following software solutions

CAST

BROADCAST

DISPLAY MANAGEMENT PLUS

## **NT+ Series**

Model	TT-5522NT-PLUS	TT-6522NT-PLUS	TT-7522NT-PLUS	TT-8622NT-PLUS	TT-9822NT-PLUS
Display					
Screen Size	55″	65"	75″	86"	98″
Landscape/Portrait Mode	Both	Both	Landscape Only	Landscape Only	Landscape Only
Backlight	LED	LED	LED	LED	LED
Display Ratio	16:9	16:9	16:9	16:9	16:9
Resolution	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels
Display Colors	1.07 billion (8 bit + FRC)	1.07 billion (8 bit + FRC)	1.07 billion (8 bit + FRC)	1.07 billion (8 bit + FRC)	1.07 billion (8 bit + FRC)
Brightness Center Brightness	Without cover glass	Without cover glass	Without cover glass	Without cover glass	Without cover glass
	>400 cd/m <sup>2</sup>	>400 cd/m <sup>2</sup>	>400 cd/m <sup>2</sup>	>400 cd/m <sup>2</sup>	>400 cd/m <sup>2</sup>
Contrast	Dynamic 5000:1 Static 1200:1	Dynamic 5000:1 Static 1200:1	Dynamic 5000:1 Static 1200:1	Dynamic 5000:1 Static 1200:1	Dynamic 5000:1 Static 1200:1
Response Time	8 ms	8 ms	8 ms	8 ms	8 ms
/iewing Angle	178°	178°	178°	178°	178°
ifetime Hours	≥ 50,000 hours	≥ 50,000 hours	≥ 50,000 hours	≥ 50,000 hours	≥ 50,000 hours
peakers					
Position	Downward	Downward	Downward	Downward	Downward
lax Power Output	(2) 15W	(2) 20W	(2) 20W	(2) 20W	(2) 20W
ransportation/Storage					
utline Dimension	50 x 29 x 3 in	58 x 34 x 4 in	70 x 39 x 4 in	77 x 44 x 4 in	TBD
acking Dimension	55 x 33 x 8 in	63 x 39 x 8	72 x 43 x 9	82 x 49 x 10	TBD
et Weight	40 lbs	TBD	73 lbs	TBD	TBD
ross Weight	56 lbs	TBD	102 lbs	TBD	TBD
ESA Mount stallation position	400 x 400 mm	600 x 400 mm	800 x 400 mm	800 x 400 mm	800 x 600 mm
nstallation Method					
lounting Options	Wall-mounted, Mobile Stand				
mall form factor omputer VESA	No	Yes	Yes	Yes	Yes
mbedded Operating System	1				
AM	4GB	4GB	4GB	4GB	4GB
OM	32GB	32GB	32GB	32GB	32GB
ndroid Version	11.0	11.0	11.0	11.0	11.0
peciality					
/i-Fi Module (Optional)		Pluggable Wi	-Fi module, Wi-Fi 6 and BlueT	ooth 5.2 capable	
irmware update	USB, OTA				
	(1) Power Button				
			· · ·		
Back Button		Up,	(1) Power Button Rocker switch for power Down, Left, Right, OK, Return	, Menu	
ack Button		Up,	Rocker switch for power	, Menu	
		Up,	Rocker switch for power Down, Left, Right, OK, Return	, Menu	
ack Button continuous Use Time		Up,	Rocker switch for power Down, Left, Right, OK, Return	, Menu	



950 W Bethany Drive, Suite 330 Allen, TX 75013 Toll-Free: 888-233-0868 Local: 972-468-9728 sales@newline-interactive.com www.newline-interactive.com