

ZH350ST

Ultra-compact high brightness Full HD 1080p laser projector





- Bright Full HD 1080p DuraCore laser projector 3500 lumens and IP6X certified
- Ultra compact and short throw lens for easy installation 360-degree and portrait projection
- DuraCore laser technology 30,000 hours maintenance-free laser light source
- Designed with the environment in mind -DuraCore laser technology cuts power consumption and ensures a long product lifespan



The ZH350ST is one of Optoma's most compact, hassle free Full HD 1080p DuraCore laser projectors to date. This short throw 3500lumen projector is built for maintenance-free continuous operation up to 30,000 hours, while its small and lightweight footprint makes it 34% smaller than the previous generation, offering flexible installation in virtually any orientation and location.

Specifications

EAN: 5055387666795 Colour: White

EAN: 5055387666795, Colour: W	
UPC: 796435 44 657 4, Colour: \	White
Display/image	
Display technology	DLPM
Resolution	1080p Full HD (1920x1080)
Brightness	3,500 lumens
Contrast ratio	300,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9,16:10
	+/-30°
Keystone correction - horizontal	47-30
	. / 00%
Keystone correction - vertical	+/-30°
Has vertical auto keystone	Yes
correction	
Displayable colors (millions)	1073.4
Horizontal scan rate	15 ~ 140Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	75%
Screen size	30" ~ 300" diagonal
Lamp info	oo oo oogonaa
	looor
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	0.496:1
Projection distance	11.81" - 129.92"
Zoom type	Manual
Focal length (mm)	7.51
Native offset	116%
Connectivity	
Connections	Inputs 2 x HDMI 2.0
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
	Control 1 x RS232
Conoral	
	004D
Noise level (typical)	32dB
Noise level (max)	34dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz
	SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,
	720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
	Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D)
3D compatibility	
3D compatibility	720p50 / 60
3D	3D ready
3D Security	3D ready Security bar, Kensington Lock, Password protected interface
3D Security IP rating	3D ready Security bar, Kensington Lock, Password protected interface IP6X
3D Security IP rating	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,
3D compatibility 3D Security IP rating OSD / display languages	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian,
3D Security IP rating	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian,
3D Security IP rating	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),
3D Security IP rating DSD / display languages	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
3D Security IP rating OSD / display languages 24/7 operation	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes
3D Security IP rating OSD / display languages 24/7 operation	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes
3D Security IP rating OSD / display languages 24/7 operation 360° operation	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes
3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes
3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m
3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Card style 1
3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Card style 1 15W
3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Card style 1 15W AC power cord
3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Card style 1 15W AC power cord Remote control
3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Card style 1 15W AC power cord Remote control 2x AAA batteries
3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker in the box	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Card style 1 15W AC power cord Remote control 2x AAA batteries Basic user manual
3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Card style 1 15W AC power cord Remote control 2x AAA batteries Basic user manual 8.60ms
3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Card style 1 15W AC power cord Remote control 2x AAA batteries Basic user manual
3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Card style 1 15W AC power cord Remote control 2x AAA batteries Basic user manual 8.60ms
3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Optional wireless models Power	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Card style 1 15W AC power cord Remote control 2x AAA batteries Basic user manual 8.60ms
3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Optional wireless models Power Power supply	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes Yes O°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Card style 1 15W AC power cord Remote control 2x AAA batteries Basic user manual 8.60ms UHDCast Pro
3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Optional wireless models Power Power supply Power consumption (standby)	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Card style 1 15W AC power cord Remote control 2x AAA batteries Basic user manual 8.60ms UHDCast Pro 100V ~ 240V, 50-60Hz <0.5W
3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Optional wireless models Power Power supply Power consumption (standby) Power consumption (min)	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 9es 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Card style 1 15W AC power cord Remote control 2x AAA batteries Basic user manual 8.60ms UHDCast Pro 100V ~ 240V, 50-60Hz <0.5W 98W
3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Optional wireless models Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max)	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Card style 1 15W AC power cord Remote control 2x AAA batteries Basic user manual 8.60ms UHDCast Pro 100V ~ 240V, 50-60Hz <0.5W
3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Optional wireless models Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Card style 1 15W AC power cord Remote control 2x AAA batteries Basic user manual 8.60ms UHDCast Pro 100V ~ 240V, 50-60Hz <0.5W 98W 139W
3D Security IP rating OSD / display languages 24/7 operation 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Optional wireless models Power Power consumption (standby) Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions Dimensions (W x D x H)	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Card style 1 15W AC power cord Remote control 2x AAA batteries Basic user manual 8.60ms UHDCast Pro 100V ~ 240V, 50-60Hz <0.5W 98W 139W
3D Security IP rating	3D ready Security bar, Kensington Lock, Password protected interface IP6X 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes Yes 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m Card style 1 15W AC power cord Remote control 2x AAA batteries Basic user manual 8.60ms UHDCast Pro 100V ~ 240V, 50-60Hz <0.5W 98W 139W







Copyright © 2023 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas InstrumentsTM. All other trademarks are the property of their respective owners. All specifications subject to change at any time. 01032023014141