

ZK810TST

High brightness professional 4K UHD laser projector



- **8600 lumen 4K UHD DuraCore laser projector - High brightness for immersive installations**
- **Full motorised lens shift - Ideal for a simple set-up**
- **Dust resistant - Independently tested, IP5X certified**
- **Long life - Delivers 30,000 hours of virtually maintenance free operation**



Spectacular 4K UHD image quality, low maintenance and ultimate reliability

The ZK810TST 4K UHD laser projector is perfect for fixed installations within education, museums, houses of worship, large venues, simulation or immersive applications.

Delivering an astonishing 30,000 hours, the ZK810TST combines a long-lifetime light source and an independent IP5X-certified optical engine for 24/7 operation capabilities, offering truly maintenance-free projection.

Specifications

UPC: 796435 44 722 9, EAN: 5055387667969, Colour: Black



Display/image

Display technology	DLP™
Resolution	UHD (3840x2160)
Brightness	8,600 lumens
ANSI brightness	7,200
Contrast ratio	3,000,000:1
Contrast ratio - full on/off	1,100:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-15°
Displayable colours (millions)	1073.4
Horizontal scan rate	15.375~91.146Khz
Vertical scan rate	24~85Hz
Uniformity	95%
Screen size	0.76m ~ 25.4m (30" ~ 1000") diagonal

Lamp info

Light source type	DuraCore MultiColor Laser
LASER life	30,000 hours

Optical

Throw ratio	0.65:1 ~ 0.75:1
Projection distance (m)	0.7m - 16.6m
Zoom	1.15
Zoom type	Motorised
Focal length (mm)	9.69~11.19
Lens shift	Vertical: +/-50%, Horizontal: +/-18%
Lens shift	Yes - {{downloads_link}}

Connectivity

Connections	Inputs 2 x HDMI 2.0, 1 x USB-B service, 1 x 3D sync, 1 x Wired remote Outputs 1 x HDMI 2.0, 1 x USB-A power 1.5A, 1 x Audio 3.5mm, 1 x 3D sync Control 1 x HDBaseT 4K, 1 x RJ45, 1 x 12V trigger, 1 x RS232
-------------	--

LAN - wireless networking

No

General

Noise level (min)	34dB
Noise level (max)	38dB
3D	Full 3D
Security	Security bar, Kensington Lock
IP rating	IP5X
OSD / display languages	11 languages: Dutch, English, French, German, Indonesian, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish
24/7 operation	Yes
360° operation	Yes
Remote control	Backlit ProAV remote
Speaker count	2
Watts per speaker	10W
In the box	QSG Back lit remote control Power cable AAA Batteries

Networking

LAN - control	Yes
LAN - wireless networking	No
LAN	Yes

Power

Power supply	AC 100 – 240 V @ 50/60 Hz
Power consumption (standby)	0.5W
Power consumption (min)	280W
Power consumption (max)	530W

Weight and dimensions

Dimensions (W x D x H) mm	486 x 432.5 x 185.5
Gross weight	18.7 kg
Net weight	15 kg

