


ZU1300

Spectacular image quality, low maintenance and ultimate reliability



- **High brightness WUXGA DLP laser projector - 14,400 lumens**
- **DuraCore laser technology - Up to 30,000 hours laser light source**
- **Dust resistant - Independently tested, IP6X certified for total reliability**
- **Installation flexibility - 7 interchangeable lens options including an ultra short throw lens**



The ZU1300 offers enhanced features such as built-in edge-blending and warping as well as 4K HDR compatibility. Part of the DuraCore laser lineup, it combines a longer-lifetime light source and an independent IP-rated dust certification for ultimate peace of mind.

Delivering up to an astonishing 30,000 hours, this projector achieves superior color rendition producing visually striking lifelike images with exceptional detail.

Specifications

UPC: 796435 44 609 3, EAN: 5055387666337, Colour: Black



Display/image	
Display technology	DLP™
Resolution	WUXGA (1920x1200)
Brightness	14,400 lumens
ANSI brightness	12,000
Contrast ratio	2,000,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3, 16:9, 16:10
Keystone correction - horizontal	+/-20°
Keystone correction - vertical	+/-20°
Uniformity	90%
Screen size	Dependent on lens
Lamp info	
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	Dependent on lens
Projection distance	Dependent on lens
Lens options	BX-CTA16- 0.36 ~ 0.36 BX-CTA17- 0.65~0.75 BX-CTA15- 0.75 ~ 0.95 BX-CTA01- 0.95 ~ 1.22 BX-CTA06- 1.22 ~ 1.53 BX-CTA03- 1.52 ~ 2.92 BX-CTA13- 2.90 ~ 5.50
Lens shift	Yes - {{downloads_link}}
Connectivity	
Connections	Inputs 2 x HDMI, 1 x 3D sync, 1 x DVI-D, 1 x HDBaseT, 1 x 3G-SDI Outputs 1 x 3D sync, 1 x HDMI Control 1 x RS232, 1 x Wired remote, 1 x USB-A power 2A, 1 x 12V trigger, 1 x RJ45
General	
Noise level (typical)	37dB
Noise level (max)	39dB
PC compatibility	HD, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible
2D compatibility	PAL (625/576i/p), SECAM, NTSC (525/480i/p), HDTV (720p, 1080i/1080p)
3D compatibility	Side-by-Side: 1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock
IP rating	IP6X
OSD / display languages	11 languages: Dutch, English, French, German, Indonesian, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish
24/7 operation	Yes
360° operation	Yes
Operating conditions	5°C~40°C/41°F~104°F, max altitude M/0ft, max humidity 10-85%
Remote control	Wired ProAV remote
In the box	AAA Battery, AC power cable 3M, Lens cover, VGA cable 1.8m, User manual CD, Quick start guide
Optional wireless models	QuickCast Bundle, QuickCast starter kit
Networking	
LAN	Yes
Power	
Power supply	100 - 240V, 50 - 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	465W
Power consumption (max)	955W
Weight and dimensions	
Dimensions (W x D x H)	19.06" x 20.83" x 8.19"
Gross weight	59.52 lbs
Net weight	46.3 lbs

