

Image Display

Display System	3-Chip 0.76" LCD
Native Chip Resolution	1920 x 1200 (WUXGA)
Maximum Brightness	7000 Lumens (ISO)
Uniformity	85%
Aspect Ratio	Native: 16:10
Dynamic Contrast Ratio	3,000,000:1

Lens

Focus	Manual Powered
Lens	f/1.7 - 2.3 (f = 26.8 - 45.5 mm)
	Horizontal: $\pm 35\%$
	Vertical: $\pm 67\%$
Lens Shift	Powered:
Optical Zoom	4.46 - 78.64' / 1.36 - 23.97 m
Throw Distance	1.61 to 2.76:1
Throw Ratio	40 - 400" / 101.6 - 1016.0 cm
Projection Size	

Features

Keystone Correction	Horizontal: $\pm 30^\circ$
Multi-Input Support (PIP/PBP)	Vertical: $\pm 25^\circ$
Ceiling Mountable	Not Specified by Manufacturer
Projection Tilt Option	Yes
Remote	Yes
	Yes

Input/Output Connectors

Inputs/Outputs	1 x RJ45 (HDBaseT) Audio, Control, Data, Video Input
HDCP Support	3 x HDMI (HDMI) Audio, Video Input
	1 x DE-15/DB-15 (VGA) Video Input
	1 x DE-15/DB-15 (VGA) Video Output
	1 x DE-9/DB-9 (RS-232) Control Input
	1 x DE-9/DB-9 Control Output
	1 x 1/8" / 3.5 mm Mini Control Input
	1 x DE-9/DB-9 Control Input
	1 x 1/8" / 3.5 mm Mini Audio Input
	1 x 1/8" / 3.5 mm Mini (HDBaseT) Audio Output
	1 x RJ45 (Ethernet) LAN
	1 x USB-A (USB 2.0) Power Output
	Version 2.3

General

Light Source	Laser Phosphor
Expected Lamp Life	Full Brightness: 20,000 Hours
	Low Brightness: 24,000 Hours
	Full Brightness: 32 dB
Fan Noise	Low Brightness: 26 dB

Security

AC Input Power

Power Consumption

Operating Temperature

Operating Humidity

Dimensions (W x H x D)

Weight

Packaging Info

Package Weight

Box Dimensions (LxWxH)

Cable Lock Slot

100 to 240 VAC, 50 / 60 Hz

Full Brightness: 435 W

Medium Brightness: 395 W

Low Brightness: 280 W

32 to 113°F / 0 to 45°C

20 to 80%

22.1 x 8.8 x 17.3" / 561.0 x 224.0 x 439.0 mm *Includi*

41 lb / 18.6 kg

53.2 lb

29.8 x 13.5 x 1.5"