Philips Monitor LCD monitor with PowerSensor



**B Line** 27" (68.6 cm) 2560 x 1440 (QHD)

275B1

# Crystal-clear vision to get more done

Get your best work done with this Philips monitor. Crystal-clear QHD gives the space and clarity for your work. Loaded with features to improve productivity and sustainability. Eye comfort features with TUV certified to reduce eye fatigue.

## **Designed for sustainability**

- Designed to meet environmental standards
- PowerSensor saves up to 70% energy costs
- · LightSensor for the perfect brightness with minimal power

## **Excellent performance**

- Crystalclear images with Quad HD 2560 x 1440 pixels
- IPS technology for full colors and wide viewing angles
- · SmartImage presets for easy optimized image settings
- Effortlessly smooth action with Adaptive-Sync technology

## Designed for the way you work

- TUV Eye Comfort certified to reduce eye fatigue
- · LowBlue Mode for easy on-the-eyes productivity
- · Less eye fatigue with Flicker-free technology
- · EasyRead mode for a paper-like reading experience
- SmartErgoBase enables people-friendly ergonomic adjustments





#### LCD monitor with PowerSensor B Line 27" (68.6 cm), 2560 x 1440 (QHD)

## Highlights

### **PowerSensor**



PowerSensor is a built-in 'people sensor' that transmits and receives harmless infrared signals to determine if user is present and automatically reduces monitor brightness when user steps away from the desk, cutting energy costs by up to 70 percent and prolonging monitor life.

## LightSensor



LightSensor uses a smart sensor to adjust the picture brightness depending on the room light conditions for the perfect picture with minimal power usage.

## **Crystalclear images**



These Philips screens deliver Crystalclear, Quad HD 2560x1440 or 2560x1080 pixel images. Utilizing high performance panels with high density pixel count, enabled by high bandwidth sources like USB-C, Displayport, HDMI, Dual link DVI, these new displays will make your images and graphics come alive. Whether you are demanding professional requiring extremely detailed information for CAD-CAM solutions, using 3D graphic applications or a financial wizard working on huge spreadsheets, Philips displays will give you Crystalclear images.

## SmartImage



SmartImage is an exclusive leading edge Philips technology that analyzes the content displayed on your screen and gives you optimized display performance. This user friendly interface allows you to select various modes like Office, Photo, Movie, Game, Economy etc., to fit the application in use. Based on the selection, SmartImage dynamically optimizes the contrast, color saturation and sharpness of images and videos for ultimate display performance. The Economy mode option offers you major power savings. All in real time with the press of a single button!

## Adaptive-Sync technology



Gaming shouldn't be a choice between choppy gameplay or broken frames. Get fluid, artifactfree performance at virtually any framerate with Adaptive-Sync technology, smooth quick refresh and ultra-fast response time.

## **TUV Rheinland Eye Comfort**



Philips display meet TUV Rheinland Eye Comfort standard to prevent eye strain caused by prolonged computer use. With TUV Eye Comfort certification, Philips displays ensure flicker-free, low blue mode, no disturbing reflections, wide viewing angle and less reduction of image quality from different angles and ergonomic stand designs for ideal viewing experience. Keep your eyes healthy and boost work productivity.

## Flicker-free technology



Due to the way brightness is controlled on LED-backlit screens, some users experience flicker on their screen which causes eye fatigue. Philips Flicker-free Technology applies a new solution to regulate brightness and reduce flicker for more comfortable viewing.

















275B1/27

## Specifications

#### **Picture/Display**

- LCD panel type: IPS technology
- Backlight type: W-LED system
- Panel Size: 27 inch / 68.6 cm
- Display Screen Coating: Anti-Glare, 3H, Haze 25%
  Effective viewing area: 596.736 (H) x 335.664 (V)
- Aspect ratio: 16:9
- Maximum resolution: 2560 x 1440 @ 75Hz\*
- Pixel Density: 109 PPI
- Response time (typical): 4 ms (Gray to Gray)\*
- Brightness: 350 cd/m<sup>2</sup>
- Contrast ratio (typical): 1000:1
- SmartContrast: 50,000,000:1
- Pixel pitch: 0.2331 x 0.2331 mm
- Viewing angle: 178° (H) / 178° (V), @ C/R > 10
- Picture enhancement: SmartImage
- Display colors: 16.7M
- Color gamut (typical): NTSC 104%\*, sRGB 107%\*
- Scanning Frequency: 30 114 kHz (H) / 48 75 Hz (V)
- Delta E: < 2 (for sRGB)
- sRGB
- Flicker-free
- LowBlue Mode
- FasyRead
- Adaptive sync

#### Connectivity

- Signal Input: DVI-D (digital, HDCP), DisplayPort 1.2, HDMI 1.4 x 1
- HDCP: HDCP 1.4 (DVI/DP/HDMI)
- USB:: USB-B x 1 (upstream), USB 3.2 x 4 (downstream with 1 fast charge B.C 1.2)
- Audio (In/Out): Audio out
- Sync Input: Separate Sync

#### Convenience

- Built-in Speakers: 2 W x 2
- · User convenience: SmartImage, Input, PowerSensor, Menu, Power On/Off
- Control software: SmartControl • OSD Languages: Brazil Portuguese, Czech, Dutch,
- English, French, Finnish, German, Greek, Hungarian, Italian, Japanese, Korean, Portuguese, Polish, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish, Ukrainian
- Other convenience: Kensington lock, VESA mount (100x100mm)
- Plug & Play Compatibility: DDC/Cl, Mac OS X, sRGB, Windows 10 / 8.1 / 8 / 7

#### Stand

- · Height adjustment: 150 mm
- Pivot: -/+ 90 degree
- Swivel: -/+ 180 degree
- Tilt: -5 ~ 35 degree

#### Power

- ECO mode: 17.5 W (typ.)
- On mode: 18 W (typ.) (EnergyStar test method)

- Standby mode: < 0.4 W (typ.)</li>
- · Off mode: Zero watts with Zero switch
- · Power LED indicator: Operation White, Standby mode- White (blinking)

75B1/27

• Power supply: Built-in, 100-240VAC, 50-60Hz

#### Dimensions

- Product with stand(max height): 613 x 537 x 205 mm
- Product with stand(max height): 24.1 x 21.1 x 8.1 inch
- Product without stand (mm): 613 x 366 x 51 mm
- Product without stand in inch: 24.1 x 14.4 x
- 2.0 inch
- Packaging in mm (WxHxD): 700 x 456 x 215 mm
- Packaging in inch (WxHxD): 27.6 x 18.0 x 8.5 inch

#### Weight

- Product with stand (kg): 6.36 kg
- Product with stand (lb): 14.0 lb
- Product without stand (kg): 4.75 kg
- Product without stand (lb): 10.45 lb
- Product with packaging (kg): 9.64 kg
- Product with packaging (lb): 21.21 lb

#### **Operating conditions**

- Temperature range (operation): 0°C to 40°C °C
- Temperature range (storage): -20°C to 60°C °C
- Relative humidity: 20%-80 %
- Altitude: Operation: +12,000ft (3,658m), Nonoperation: +40,000ft (12,192m)
- MTBF (demonstrated): 70,000 hrs (excluded backlight)

### **Sustainability**

- · Environmental and energy: PowerSensor, LightSensor, EnergyStar 8.0, EPEAT\*, TCO Certified Edge, RoHS
- Recyclable packaging material: 100 %
- Post consumer recycled plastic: 85%
- · Specific Substances: Mercury free, PVC / BFR free housing

#### **Compliance and standards**

 Regulatory Approvals: CB, EPA, FCC Class B, ICES-003, CE Mark, TUV Ergo, TUV/GS, SEMKO, CU-EAC, UKRAINIAN, TUV Eye Comfort certified

#### Cabinet

- Front bezel: Black
- · Rear cover: Black
- Foot: Black
- Finish: Texture

#### What's in the box?

- · Monitor with stand
- · Cables: HDMI cable, DP cable, Audio cable, Power
- cable
- User Documentation



Issue date 2023-03-11

© 2023 Koninklijke Philips N.V. All Rights reserved.

www.philips.com

Version: 4.0.2

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 001 72438 UPC: 6 09585 25386 5

\* "IPS" word mark / trademark and related patents on technologies

- belong to their respective owners.
- \* The maximum resolution works for either HDMI input or DP input. \* Response time value equal to SmartResponse

\* SKGB Area based on Cle1931
 \* Fast charging complies with USB BC 1.2 standard
 \* EPEAT rating is valid only where Philips registers the product. Please visit https://www.epeat.net/ for registration status in your country.
 \* The monitor may look different from feature images.

\* NTSC Area based on CIE1976 \* sRGB Area based on CIE1931