



# Clarity Matrix MultiTouch LX46HDS-L-ERO

## LCD Video Wall System

The Clarity® Matrix® MultiTouch Video Wall is an ultra-slim profile touch screen video wall ideal for public spaces or collaboration environments. Utilizing a touch kit, Clarity® Matrix® LX46HDS-L-ERO can be transformed into a Clarity Matrix MultiTouch Video Wall featuring up to 32 touch points and allows multiple users to simultaneously interact with the video wall without affecting other users. Clarity Matrix MultiTouch with Planar® ERO™ (Extended Ruggedness and Optics™) technology provides a continuous touch surface while increasing durability and optical performance. Clarity Matrix LX46HDS-L-ERO features a tiled bezel width of 5.5mm and 500 nits brightness.



SPECIFICATION	DETAIL
<b>Planar Part Number</b>	997-7219-00
<b>Technology</b>	Commercial-grade direct view LCD
<b>Diagonal</b>	46 inches
<b>Aspect Ratio</b>	16:9
<b>Native Resolution Panels</b>	1920 x 1080
<b>Tiled Bezel Width</b>	0.22" (5.5 mm)
<b>Brightness (typ)</b>	500 nits
<b>Response Time (typ)</b>	8 ms
<b>Contrast ratio (full field)</b>	3500:1
<b>Full viewing angle</b>	178°
<b>Backlight life (1/2 brightness)</b>	50,000 Hrs
<b>Mounted Depth</b>	4.4" wall to front of screen
<b>Acoustic Noise</b>	Fanless operation
<b>Heat load</b>	489 BTU per hour at 500 nit
<b>Operating temperature range</b>	5 - 40 Degrees C
<b>Operating humidity range</b>	20-90% RH non-condensing
<b>Backlight control</b>	Individual and wall control

<b>Backlight sensing and reporting</b>	At display level
<b>Display module position sensing</b>	Auto-sensing integrated
<b>Power Consumption (typ)</b>	143 watts
<b>Power supply voltage</b>	100-240 Volts AC, 50-60Hz auto switching
<b>Power Status</b>	Diagnostics LEDs, health monitoring and alerts
<b>Safety regulations</b>	Complies with EN60950, FCC Class A, CISPR22/85, CE, EU RoHS
<b>Data Inputs</b>	4 Single Link HDMI inputs, 1 DisplayPort input
<b>Control</b>	IR Remote, RS232, Ethernet (optional)
<b>Per Panel Dimensions (Including Mount)</b>	40.3" x 22.8" x 4.4" (1023.6 mm x 579.1 mm x 111.8 mm)
<b>Per Panel Weight (Including Mount)</b>	58 lbs (26.31 kg)
<b>Shipping weight</b>	162 lbs (73.48 kg)
<b>Touch Options</b>	Clarity Matrix MultiTouch Kits: MT6-6 Simultaneous Touch Points; MT32-32 Simultaneous Touch Points
<b>Touch Frame Dimensions</b>	2.6" x 2.6" x 5.3" (66.1 x66.1 x 134.3)
<b>Power for Touch System</b>	100-240V AC, 50-60 Hz
<b>OS Compatibility</b>	Windows 7, Windows XP, Mac OS X

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 4/2/2018*

*© Copyright 2018 Planar Systems, Inc. All rights reserved*