

## Connections

Connector Type	4 x HDMI input   DisplayPort input   Serial   LAN
----------------	---

## Miscellaneous

Included Accessories	Planar WallDirector Software
----------------------	------------------------------

Compliant Standards	FCC Class A certified, EN 60950, CISPR 22, RoHS
---------------------	---

## Dimensions & Weight Details

Dimensions & Weight Details	Bezel (bottom) - 0.1 in   Bezel (sides) - 0.1 in   Bezel (top) - 0.1 in
-----------------------------	---

## Environmental Parameters

Min Operating Temperature	41 °F
---------------------------	-------

Max Operating Temperature	104 °F
---------------------------	--------

Humidity Range Operating	20 - 90%
--------------------------	----------

## General

Product Type	LED-backlit LCD flat panel display
--------------	------------------------------------

Power Consumption Operational	146 Watt
-------------------------------	----------

Diagonal Class	55"
----------------	-----

Commercial Use	Yes - digital signage
----------------	-----------------------

TV Tuner	No tuner
----------	----------

TV Tuner Presence	No
-------------------	----

Video Interface	HDMI
-----------------	------

HDMI Ports Qty	4 ports
----------------	---------

PC Interface	DisplayPort
--------------	-------------

Modes	Landscape mode
-------	----------------

Width	47.8 in
-------	---------

Depth	3.6 in
-------	--------

Height	26.9 in
--------	---------

Weight	50.71 lbs
--------	-----------

## Stands & Mounts

VESA Mounting Interface	Yes
-------------------------	-----

Flat Panel Mount Interface	Yes
----------------------------	-----

## Dimensions & Weight (Shipping)

Weight (Shipping)	150 lbs
-------------------	---------

## Power

Power Device	Power supply
--------------	--------------

Nominal Voltage	AC 120/230 V (50/60 Hz)
-----------------	-------------------------

Input Voltage	AC 120/230 V (50/60 Hz)
---------------	-------------------------

## Display

Resolution	1920 x 1080
------------	-------------

Display Format	1080p
----------------	-------

Image Aspect Ratio	16:9
--------------------	------

LCD Backlight Technology	LED backlight
--------------------------	---------------

Image Contrast Ratio	3500:1
----------------------	--------

Brightness	500 cd/m <sup>2</sup>
------------	-----------------------

Viewing Angle	178°
---------------	------

Viewing Angle (Vertical)	178°
--------------------------	------

Response Time	8 ms
---------------	------

Backlight Life	50,000 hour(s)
----------------	----------------

Additional Features	Certified for 24/7 Continuous Operation, EasyAxis
---------------------	---