

## Clarity Matrix G2 MX55HDX-L LCD Video Wall System

The Clarity® Matrix® MX55HDX-L is an extreme narrow bezel 55" LCD video wall display that provides outstanding tiled visual performance, supports extended operation, and requires minimal installation space. Designed for 24x7 operation, Clarity Matrix MX55HDX-L features 800 nits brightness, LED backlight technology, and Full HD resolution making it the ideal video wall for high-impact, mission-critical applications. Clarity Matrix MX55HDX-L sets a new benchmark with a tiled bezel width of a mere 1.7mm, creating a near seamless digital canvas.



SPECIFICATION	DETAIL
Planar Part Number	997-8319
Technology	Commercial-grade direct view LCD
Diagonal	55 inches
Aspect Ratio	16:9
Native Resolution Panels	1920 x 1080
Tiled Bezel Width	0.06" (1.7 mm)
Brightness (typ)	800 cd/m <sup>2</sup> or nits
Response Time (typ)	8 ms
Contrast ratio (full field)	4000:1
Full viewing angle	178°
Backlight life (1/2 brightness)	50,000 Hrs
Mounted Depth	3.6" wall to front of screen
Acoustic Noise	Fanless operation
Heat load	660 BTU/hr
Operating temperature range	5 - 40 Degrees C
Operating humidity range	20-90% RH non-condensing
Backlight control	Individual and wall control
Backlight sensing and reporting	At display level

Display module position sensing	Auto-sensing integrated
Power Consumption (typ)	194 W
Power supply voltage	100-230V AC ± 10%, 50-60 Hz
Power Status	Diagnostics LEDs, health monitoring and alerts
Safety regulations	Complies with EN60950, FCC Class A, CISPR22/85, CE, EU RoHS
Data Inputs	4 HDMI inputs, 1 DisplayPort input
Control	IR Remote, RS232, Ethernet (optional)
Per Panel Dimensions (Including Mount)	47.72" x 26.85" x 3.54" (1212 mm x 682 mm x 90 mm)
Per Panel Weight (Including Mount)	56 lbs. (26 kg)
Shipping weight	150 lbs (68.04 kg)
Touch Options	Clarity Matrix MultiTouch Kits