



Planar PZN2710Q

27" Docking Monitor

The Planar® PZN2710Q is a 27" Quad HD USB Type - C Docking monitor with integrated docking station provides a simple and easy way to connect a PC/laptop to the monitor. The monitor enables a single USB Type C cable to deliver audio, video, data, network connectivity, daisy chain, and power delivery up to 65 watts. The Planar PZN2710Q suits nicely into education, home, office or healthcare applications.



| SPECIFICATION | DETAIL |
|--------------------------|--|
| Product Name | PZN2710Q |
| Planar Part Number | 998-2124-00 |
| Viewable Size | 27" diagonal (23.53" x 13.21") |
| Aspect Ratio | 16:9 |
| Contrast Ratio (typ) | 1000:1 |
| Viewing Angle (typ) | 178° Horizontal and Vertical |
| Response Time (typ) | 6 ms (GTG) |
| Brightness (Typical) | 300 cd/m ² |
| Display Type | IPS LCD Active Matrix Flat Panel Display (TFT) |
| Display Resolution | 2560 x 1440 WQHD |
| Tilt Range | -5° to +20° |
| Palette | 16.7 million colors |
| Pixel Pitch | 0.2331 mm |
| Refresh Rate | 48-75Hz (60Hz recommended) |
| Dimensions (W x H x D) | 24.2" x 20.5" x 9.1" (612.84 mm x 519.39 mm x 229.63 mm) |
| Dimensions without Stand | 24.2" x 20.5" x 2.1" (612.84 mm x 519.39 mm x 52.3 mm) |
| Panel Depth | 2.1" (52.3 mm) |
| Display Weight | 13.6 lb/6.16 kg (9.2 lb/ 4.17 kg without stand) |
| Shipping weight | 16.5 lb (7.5 kg) |
| Video Inputs | USB Type C (DisplayPort Alt Mode), DisplayPort, HDMI |

| | |
|--|--|
| Video Outputs | DisplayPort |
| HDCP | Yes |
| Audio Output | Integrated 2W/channel stereo speakers, headphone jack |
| External Connections | USB Type C, HDMI 19-pin, DisplayPort 20-pin, 3.5mm headphone out, USB 3.2 Gen 1 (Type A) x 3, RJ45, DisplayPort 20-pin (out) |
| USB | USB-C x 1 (Upstream) (5Gbps), USB3.2 Gen1 x 3 (Downstream) |
| USB C Power Delivery | USB C (Up to 65W) (5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A) |
| RJ45 | Ethernet LAN (10M/100M/1000M) |
| Compatibility | PC and Mac® (adapter may be required for Mac) |
| Power Supply | External (DC power) |
| Power Consumption (max) | 35W typical (<0.5W standby) |
| Power Requirements | AC 100/240 VAC |
| Operating Temperature | 0° to +40°C (32° to 104°F) |
| Humidity | 10 - 85% RH (non-condensing) |
| Mount | Built-in 100 mm VESA, back |
| Product Approvals | cTUVus, CE , FCC-B, RoHS II |
| Recommended Usage | Up to 16 hours per day |
| Service and Support | 3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only). Please see warranty document for more details and for replacement procedures outside the US. |
| Options / Features | IPS panel, Wide color consistent viewing angle, Discreet branding, Height adjustment: 4.3" (120cmm), Swivel range 60° (30° left, 30° right), Pivot 90°, Anti-glare coating ,Multi-language display, On screen display (OSD), Kensington® Security Slot |
| Blue Light Reduction | Yes |
| Flicker Free | Yes |
| In the Box | PZN2710Q 27" LCD Monitor, Power Cord, DP Cable, USB Type-C Cable, User's Guide |
| UPC | 8 10689 00803 3 |
| Recommended Daisy Chain Monitor | PXN2710Q (998-2123-00) |

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 12/16/2020

© Copyright 2020 Planar Systems, Inc. All rights reserved