

PP-VIB

Vibration Reducing Adapter

Color: Black

Weight 5.00 lb. | 2.3 kg

Weight Capacity 50 lb. | 22.7 kg

Pole Diameter 0.00 in. | 0 mm

Downloads at Mounts.com



[Data Sheet](#)



[Bid Specification Document](#)



[Installation Manual](#)



[Dimensional Drawing](#)



[CAD File](#)



50 lb.

DESCRIPTION

The Vibration Reducing Adapter (PP-VIB) absorbs vibrations from outside disruptions to keep the display image steady. Large rubber dampers inside the PP-VIB absorb shock caused from outside activities such as slamming doors or equipment motors. This adapter includes an integrated coupler that fits any 1.5" NPT pipe (not included). Attach the adapter to any ceiling stud, solid ceiling surface, or Premier Mounts' PP-FCMA ceiling adapter, secure the 1.5" NPT pipe (not included), then install the mount to the pipe.

FEATURES

- Inner rubber dampers absorb vibrations near the mount
- Integrated coupler adapts to 1.5" NPT pipe
- Mounts to a ceiling stud, a solid ceiling surface, or Premier Mounts' PP-FCMA ceiling adapters



PP-VIB

Vibration Reducing Adapter

DOWNLOAD FULL SIZE CAD FILES AND DIMENSIONAL DRAWINGS AT MOUNTS.COM

RELATED PRODUCTS FOR PP-VIB

- 

SPI-PRO
SpiroLock™ Projector Mount with 1.5 in. NPT Coupler
- 

PBC-UMS
Universal Projector Mount with Integrated Coupler
- 


PP-FCMA
Full-Tile False Ceiling Adapter
- 


PP-FCMA-QL
Full-Tile False Ceiling Adapter with Quick-Lock Cable
- 


APP-2446
Adjustable-Height Pipe Adapter with 1.5 in. NPT Pipe


[MORE AT MOUNTS.COM](http://MOUNTS.COM)


SIMILAR PRODUCTS


- 

PP-VIB
Vibration Reducing Adapter
- 

PP-USA
Unistrut Adapter
- 

PP-TL
Vaulted Ceiling Adapter
- 

AST-2446-2
Adjustable-Height Ceiling Adapter (24 inch-46 inch)
- 

PP-ITC48P2
4 inch-8 inch I-Beam Adapter with 2 inch Pipe Nipple
- 

EUCB
2 in. Column to 1.5 in. NPT Adapter

[MORE AT MOUNTS.COM](http://MOUNTS.COM)

