VL NDI® | HX ZCAM

Share Your Vision



Model Number:

PTVL-NDI-ZCAM (white) http://ptzoptics.com/ndi/

PTZOPTICS

Broadcast & Conference Camera

The PTZOptics VL-NDI ZCAM is a 1080p camera with wide angle lens for capturing HD images at short distances. With support for NDI|HX, 3G-SDI, and IP streaming (H.264, H.265, & MJPEG), this camera is ideal for broadcasting high definition video signals for broadcast, recording, or video conferencing applications.

KEY FEATURES

- Panasonic 1/2.7" HD CMOS Sensor
- 3G-SDI & NDI® | HX High Definition Video Output
- H.264, H.265, & MJPEG IP streaming output (dual stream)
- AAC stereo unbalanced audio encoding over IP & NDI
- Full 1920x1080p HD Resolutions up to 60 FPS via SDI (30 FPS over NDI)
- 3G-SDI, & NDI or IP streaming (Both simultaneously)
- Std 1/4-20 female thread for camera mounting (top & bottom)
- PoE (Power over Ethernet) or 12VDC
- RTMP, RTSP, and NDI|HX
- C/CS Type lens mount
- RS485 and IP remote camera control
- Hold left button on Menu Navigation for 5+ seconds to toggle Dynamic or Static IP addressing
- 5-year warranty
- Photobooth capable

WHAT'S IN THE BOX

Box Camera 4X Zoom Wide Angle Lens Power Adapter Quick Start Guide



| Camera & Lens | |
|----------------------------|--------------------------------|
| Video CMOS Sensor | 1/2.7" CMOS, 2.07 Mega Pixels |
| | 1080p 60/50/30/25, 1080i 60/50 |
| Frame Rate | 720p 60/50 |
| | (IP Stream limited to 30 fps) |
| Included Lens | F3.8mm ~ 13mm, F1.4+ |
| Incl. Lens Zoom | 4X Optical Zoom |
| Incl. Lens Field of View | 72° |
| Min Lux | 0.05 Lux (@F1.8, AGC ON) |
| Shutter Speed | 1/30s - 1/10000s |
| SNR | ≥55dB |
| Vertical Flip & Mirror | Supported |
| Incl. lens H Angle of View | 21° (tele) - 72° (wide) |
| Incl. lens V Angle of View | 12° (tele) - 45° (wide) |
| Working Environment | Indoor |

| Rear Board | |
|------------------------|--|
| Video Output Interface | 3G-SDI, NDI HX |
| Network Interface | RJ45 (PoE 802.3af) |
| Audio Interface | AAC unbalanced stereo (NDI HX only) |
| Communication | RS485 VISCA, Pelco-D, Pelco-P |
| Baud Rate | 2400/4800/9600 bits |
| Power Supply Interface | JEITA type Power Adapter (DC IN 12V) |
| Electrical Index | |
| Power Supply | 12W (Max) or PoE 802.3af |
| Input Voltage | 12V DC (10.8 - 13.0V DC) or PoE 802.3af |
| Physical Specs. | |
| Dimension (in.) | 2.8W x 2.4H x 5.94D (8.25 w/ incl. lens) |
| Dimensions (mm.) | 72W x 61H x 151D (210 w/ incl. lens) |
| Camera Weight (lbs.) | 0.85 (1.05 w/ incl. lens) |
| Camera Weight (kg.) | 0.39 (0.48 w/ incl. lens) |