


UNIFI HUDDLE™



UNIFI HUDDLE™

The Salamander Designs Unifi Huddle™ Tables provide the latest in high-quality, customizable solutions so teams can gather quickly and collaborate more easily. Unifi Huddles consist of two models that provide the latest in table solutions to accommodate today's modern offices and impromptu meetings.

Both designs are easy to specify for rapid deployment and offer innovative solutions to support and manage today's technology. Ultra simple to install in just minutes, Unify is built to last and a future-proof design allows technology updates easily.





UNIFI HUDDLE™


Ideal for 2 to 5 people seated, Unifi offers select mounting solutions to support virtually any unified communication technology. A premium-grade cabinet features storage for larger AV systems with quick access and easy cable management. Other thoughtful options include power distribution and cooling systems.



Four table top options.

UNIFI HUDDLE™ LITE

Since one size doesn't fit all, the smaller Unifi Huddle Lite accommodates 2 to 3 people at cafe-height and is ideal for a fast-paced environment where people gather often in an impromptu manner. The Unifi Lite is available with or without integrated display mount and features a unique under table storage base is easily accessible for small AV systems.









Wire Management

Throughout open cabinet, back with fully open interior and raceway up to display and to table

Customize Your Unifi Huddle™

with optional mounts, cut-ins and interior accessories for a complete turnkey video conference solution.



VIDEO CONFERENCE -



A. Universal Single or *Dual Display Mounts with Adjustable Positions

* 338 Cabinet Model Only



B. Speaker/Camera Mount

Speaker sold seperately



C. Tech Shelf
Camera sold seperately



CONNECTION PORTS -

Ports can be placed in various locations throughout table and cabinet. Reference page 7 for location specs.



Plush Mount 110v Power and Dual USB Charge

#FI/CP5/BK - Black



E. Pop-up Wireless Qi Charger with Triple USB Charging

#FI/CP4/BK - Black



F. Cable Port

#FI/CP2/BK - Black #FI/CP2/SN - Satin Nickel



G. Under Table Dual USB Charging Dock

#FI/CP8/BK - Black



H. Popup Charge & Connect

#FI/CP7/BK



Pen Holder

#FI/CP6/BK



Specifiy Your Own Device with a Custom Cut-In



CABINET INTERIORS



I. Vertical Rack Mount



J. 1RU Vertical, Rack Mounted Cooling Kit



1RU Multi-Port Rack Mounted Power Distribution Unit







Cabinet Finishes	Single Display	Dual Display	No Display	4'x5' Table Top
Warm White Gloss (Laminate)	D1/338AM1/SN/GW/BK	D1/338AM2/SN/GW/BK	D1/338A/SN/GW/BK	Warm White TP4860A/C/WW
Slate Gray Matte (Laminate)	D1/338AM1/SN/SG/BK	D1/338AM2/SN/SG/BK	D1/338A/SN/SG/BK	Slate Gray TP4860A/C/SG
Gray Oak (Veneer)	D1/338AM1/SN/GO/BK	D1/338AM2/SN/GO/BK	D1/338A/SN/GO/BK	Satin Black TP4860A/C/BK
Black Oak (Veneer)	D1/338AM1/SN/BO/BK	D1/338AM2/SN/BO/BK	D1/338A/SN/BO/BK	1/2" Solid TP4860A/C/BK1
Wengé Oak (Veneer)	D1/338AM1/SN/WO/BK	D1/338AM2/SN/WO/BK	D1/338A/SN/WO/BK	Compact Core
Natural Oak (Veneer)	D1/338AM1/SN/NO/BK	D1/338AM2/SN/NO/BK	D1/338A/SN/NO/BK	_

Cabinet: 65"W (1651mm) x 31"H (787mm) (65" (1651mm) w/mount) x 12"D (305mm)

Table: 60"L (1524mm) x 48"W (1219mm) x 29"H (736mm)

UNIFI HUDDLE™ LITE



2-3 PERSON



	Single Display	No Display
Warm White	UHL40AM1/G/S/WW	UHL40A/G/S/WW
Slate Gray	UHL40AM1/G/S/SG	UHL40A/G/S/SG
Satin Black	UHL40AM1/G/S/BK	UHL40A/G/S/BK
1/2" Solid Black Compact Core	UHL40AM1/G/S/BK1	UHL40A/G/S/BK1

Table: 48"L (1219mm) x 48"W (1219mm) x 39"H (990mm)



Butter-knife Edge 3/4" Seamless Powder-Coated MDF



Square Edge 1/2" Solid Black Compact Core



Custom HPL Laminates Available Call or details.

Specifications

VIDEO CONFERENCE

Display Mounts

Select Table Model

- Universal single or dual display mount with adjustable positions
- Holds displays up to: Huddle: 175 lbs (80 kg) Huddle Light: 110 lbs (50 kg)
- Single: VESA 200 x 200 400 x 600
- Dual: VESA 200 x 200 500 x 800
- Adjustable Center Line of Screen: 59" (1499mm) / 57 (1448mm) /55.25"(1403mm) / 53.375" (1356mm) / 51.5" (1308mm)

Speaker/Camera Mount

#FI/CP2/BK

- Fully adjustable height
- Mount above or below display
- Accommodates most video/audio conference systems
- Universal mounting plate pattern: 0-16" (0-410mm)
- Max weight capacity of 25 lbs (11 kgs)

Tech Shelf

#FI/CP2/BK - Single Shelf #FI/CP2/BK - Dual Shelf

Call for Custom Sizes

- Fully adjustable height
- Mount above or below display
- Max weight capacity of 5 lbs (2 kgs)
- Single Shelf: 7"W (178mm) x 5.75"D (146mm) x .25"Th (6mm)
- Dual Shelf: 26.25"W (667mm) x 6.75"D (171mm) x .5"Th (13mm)

CABINET INTERIORS

Vertical Rack Mounts

#FI/RM/VR/3U - 3RU #FI/RM/VR/5U - 5RU

- 3 and 5 rack units of vertical mounted, knob up component storage (total 15RU)
- Threaded for 10-32 screws
- Black powder coated steel
- Lift and load design for easy install
- 10-32 threaded fasteners

1RU Vertical, Rack Mounted Cooling Kit

#SA/IUAC - Black

- Airflow: 40 to 180 CFM | Noise: 9 to 32 dBA
- 180 cfm of airflow at max efficiency maintains a 20 degree rise of up to 3750 btu of electronics
- 19"W (482mm) x 13.5"D (343mm) x 1.75" Th (44mm)
- Probe Length: 72"
- Power Consumption: 8 W, 0.67 A
- Power In: 100 to 240V AC
- RoHS and CE Certified

1RU Multi-Port Rack Mounted Power Distribution Unit

#FI/RM/PDU - Black

- 8 Rear Ports, 1 Front Port
- Maximum Output Current: 15 Amps
- Spike Protection Mode: Line to neutral
- Energy Dissipation: 170 Joules
- Peak Impulse Current: 12,000 Amps
- Maximum Continuous Operating Voltage: 130 VAC RMS
- 9"W (228mm) x 3.75D" (95mm) x 1.75" Th (44mm)
- Safety Agency Listing: cTUVus Certified

CONNECTION PORTS SPECS & CUT-IN LOCATIONS



3" Round Flush mount 110v Power and Dual USB Charge

#FI/CP5/BK - Black

- 1 Outlet, AC 125V 15A max
- 5V 4.2A USB module with 2 ports
- Bore 3" (76.2mm) hole for installation
- 10' (3058mm) SJT 14 AWG*3C power cord
- UL Certified
- Cut-In Locations 1, 2, 3, 5, 6



Pop-up Wireless Qi Charger with Triple USB Charging

#FI/CP4/BK - Black

- Power Input: DC 5V, 6A max
- Wireless Charger: 5 watts max
- USB Charger: 1 x 2.4A (12 watts) max and 2 x 1A (5 Watts) Max
- Wireless Charging Distance: 6mm max
- Qi V1.2.4 Certified
- UL, cUL, FCC ID, RoHS Certified
- Cut-In Locations 1, 2, 3, 4, 5, 6




3-3/8" Round Cable Port


#FI/CP2/BK - Black #FI/CP2/SN - Satin Nickel

- Split Body Design for Plug and Wire Pass Through
- Cut-In Locations 1, 2, 3, 4, 5, 6

UNIFI HUDDLE




UNIFI HUDDLE LITE



4x6 Popup Charge & Connect

#FI/CP7/BK

- Aluminum Housing
- 1 Grounded AC Outlet, 125 V 12A rating5V 4.2A USB module with 2 ports
- 1 HDMI coupler
- 1 HDMI couple
- 1 Ethernet RJ45 Coupler power cord
- UL Certified
- Cut-In Locations 1, 2, 3, 4, 5



Under Table Dual USB Charging Dock

#FI/CP8/BK - Black

- Dual 5V DC 2.1A (10.5 Watts) USB charging ports
- Input 5VDC 4.2A wall plug adapter with 8' lead
- Blue LED back-lighting
- UL Pending
- Cut-In Locations 7A, 7B, 7C, 7D

CUSTOMMADE EASY

Salamander specializes in custom designing and manufacturing high-performing furniture solutions for complex projects.

Call us for a free design consultation.



SALAMANDER DESIGNS 811 Blue Hills Avenue Bloomfield, CT 06002

salamandercommercial.com

custom@salamanderdesigns.com 800.535.9910



Salamander technology partners provide solutions that, when combined with the Unifi Huddle, create an ecosystem of products that create the perfect interactive, collaboration solution for every corporate environment.

