

Healthcare Display

HCU7030 series

Foster a comfortable, patient-centric experience

Modern day hospitals are turning to premium entertainment and infotainment technologies that focus on the patient experience, as well as workflow efficiencies for nursing staff.

Samsung's HCU7030 healthcare series allows for patient-staff connectivity, and gives patients and visitors an experience that makes them feel at home. Equipped with an integrated pillow speaker interface, Samsung's HCU7030 series allows patients to enjoy clear audio and control of the TV right at their bedside. The displays are UL-certified for safe usage in any hospital or healthcare facility. WebRTC enabled to facilitate secure, real-time communications over the network.

Key features



Crystal Processor 4K

Powerful 4K upscaling delivers any content in up to 4K resolution.



Pro:Idiom™ DRM HD Content Decryption

The HCU7030 series is equipped with Pro:Idiom MPEG4 technology to offer your patients premium HDTV content from cable, satellite or video-on-demand services with no optional cards or external box needed.



Universal Pillow Speaker Interface

An easy-to-use interface is built right into the TV, to utilize with multiple brands and models of pillow speakers.



UL-Listed for Hospital Use

The Samsung Healthcare Series displays are specifically engineered to meet the stringent requirements for use in hospital environments. They are manufactured in accordance with UL's published and nationally recognized Standards for Safety.



Improved Tizen Enterprise Platform for more streamlined operations.

Samsung's latest Tizen Enterprise Platform allows for greater flexibility for Interactive Patient Care Platform (IPC) solutions, and allows System Integrators to implement the platform without the need for a set-top box.



Samsung's LYNK Cloud Device and Content Management Solution

The HCU7030 is natively compatible with Samsung's LYNK Cloud Solution, allowing IT Managers to control their fleet of displays from virtually anywhere. Premier content management services make it easy to create, schedule and deploy your hospital's information to patients and visitors.

Specifications

	Model	43"	50"	55"	65"	75"
D'anta	Product	Crystal UHD	Crystal UHD	Crystal UHD	Crystal UHD	Crystal UHD
Display	Resolution	3,840 x 2,160	3,840 x 2,160	3,840 x 2,160	3,840 x 2,160	3,840 x 2,160
Video	Picture Engine	Quantum Processor 4K Lite	Quantum Processor 4K Lite	Quantum Processor 4K Lite	Quantum Processor 4K Lite	Quantum Processor 4K Lite
	Film Mode	Yes	Yes	Yes	Yes	Yes
	Picture Clarity	Yes	Yes	Yes	Yes	Yes
	HDR (High Dynamic Range)	HDR	HDR	HDR	HDR	HDR
	HDR10+	Support	Support	Support	Support	Support
	HLG (Hybrid Log Gamma)	Yes	Yes	Yes	Yes	Yes
	Contrast	Mega Contrast	Mega Contrast	Mega Contrast	Mega Contrast	Mega Contrast
	Color	Pur Color	Pur Color	PurColor	Pur Color	Pur Color
	Viewing Angle (H/V)	178/178	178/178	178/178	178/178	178/178
	Contrast Enhancer	Yes	Yes	Yes	Yes	Yes
Audio	Dolby Decoder	MS12 2CH	MS12 2CH	MS12 2CH	MS12 2CH	MS12 2CH
	Object Tracking Sound	OTS Lite	OTS Lite	OTS Lite	OTS Lite	OTS Lite
	Sound Output (RMS)	20W	20W	20W	20W 2CH	20W
	Speaker Type Bluetooth Audio	2CH Yes	2CH Yes	2CH Yes	Yes	2CH Yes
	VESA Mount	200 x 200 mm	200 x 200 mm	200 x 200 mm	400 x 300 mm	400 x 400 mm
Vesa	VESA Modrit VESA Screw Size	M8	200 x 200 mm	200 x 200 IIIIII	400 X 300 IIIIII	400 X 400 IIIIII
	VESA Screw Depth	20-22	20-22	20-22	20-22	20-22
	Mobile to TV - Mirroring, DLNA	Yes	Yes	Yes	Yes	Yes
Smart Feature	Sound Mirroring	Yes	Yes	Yes	Yes	Yes
	Ambient Mode	Yes	Yes	Yes	Yes	Yes
	Voice Guide				res Igal Portuguese, Romanian, Slovak, Sw	
General Feature	Auto Channel Search	Yes	Yes	Yes	Yes	Yes
	Auto Power Off	Yes	Yes	Yes	Yes	Yes
	Caption (Subtitle)	Yes	Yes	Yes	Yes	Yes
	Connect Share™	Yes	Yes	Yes	Yes	Yes
	EPG	Yes	Yes	Yes	Yes	Yes
	OSD Language	English, Spanish, French	English, Spanish, French	English, Spanish, French	English, Spanish, French	English, Spanish, French
	V-Chip	Yes	Yes	Yes	Yes	Yes
	IPv6 Support	Yes	Yes	Yes	Yes	Yes
	Digital Broadcasting	ATSC/ClearQAM	ATSC/ClearQAM	ATSC/ClearQAM	ATSC/ClearQAM	ATSC/ClearQAM
System	Analog Tuner	Yes	Yes	Yes	Yes	Yes
Hospitality Feature	Samsung LYNK™ Cloud	Yes	Yes	Yes	Yes	Yes
	TEP	Yes	Yes	Yes	Yes	Yes
	Hospitality Plug&Play (Easy Set-up)	Yes	Yes	Yes	Yes	Yes
	Power On Mode	Yes	Yes	Yes	Yes	Yes
	Hotel Channel List	Yes	Yes	Yes	Yes	Yes
	Channel Menu Display	Yes	Yes	Yes	Yes	Yes
	Mixed Channel List (ATSC, DVB-T/T2/C/S2, Analog)	Yes	Yes	Yes	Yes	Yes
	My Channel	Yes	Yes	Yes	Yes	Yes
	Energy Saving Mode (BLU Control)	Yes	Yes	Yes	Yes	Yes
	Multi-code IR USB Cloning	Ready (Extra Accessory RCU Needed) Yes	Ready (Extra Accessory RCU Needed) Yes	Ready (Extra Accessory RCU Needed) Yes	Ready (Extra Accessory RCU Needed) Yes	Ready (Extra Accessory RCU Needed) Yes
	Wake-up Timer (Alarm)	Yes	Yes	Yes	Yes	Yes
	Samsung LYNK™ DRM	Yes	Yes	Yes	Yes	Yes
	Pro:Idiom™	Yes	Yes	Yes	Yes	Yes
	UL Certification For Hospital Usage	Yes	Yes	Yes	Yes	Yes
	Security Mode	Yes	Yes	Ves	Vec	Vos
Input and Output	USB	2	2	2	2	2
	Ethernet (LAN)	1	1	1	1	1
	Digital Audio Out (Optical)	1	1	1	1	1
	RF In (Terrestrial/Cable Input/Satellite Input)	1/1 (Common Use For Terrestrial)/0	1/1 (Common Use For Terrestrial)/0	1/1 (Common Use For Terrestrial)/0	1/1 (Common Use For Terrestrial)/0	1/1 (Common Use For Terrestrial)/
		Supports Stereo Jack to RS232	Supports Stereo Jack to RS232	Supports Stereo Jack to RS232	Supports Stereo Jack to RS232	Supports Stereo Jack to RS232
	Ex-Link (Supports RS-232C Gender)	Adapter	Adapter	Adapter	Adapter	Adapter
	HDMI A/Return Ch. Support	eARC/ARC	eARC/ARC	eARC/ARC	eARC/ARC	eARC/ARC
	WiFi	Yes (WiFi5)	Yes (WiFi5)	Yes (WiFi5)	Yes (WiFi5)	Yes (WiFi5)
	Anynet+ (HDMI-CEC) Pillow Speaker Jack Input jumper pin	Yes 1/8 (3.5mm) 3-conductor stereo phone pin	Yes 1/8 (3.5mm) 3-conductor stereo phone pin	Yes 1/8 (3.5mm) 3-conductor stereo phone pin	Yes 1/8 (3.5mm) 3-conductor stereo phone pin	Yes 1/8 (3.5mm) 3-conductor stereo phone pin
	RJ12/IR Pass Through	Yes	Yes	Yes	Yes	Yes
	Front Color	Black	Black	Black	Black	Titan Gray
Design	Bezel Type	3 Bezel-less	3 Bezel-less	3 Bezel-less	3 Bezel-less	3 Bezel-less
Eco	Eco Sensor	Yes	Yes	Yes	Yes	Yes
Power	Power Supply (V)	AC110-120V 50/60Hz	AC110-120V 50/60Hz	AC110-120V 50/60Hz	AC110-120V 50/60Hz	AC110-120V 50/60Hz
	Power Consumption (Max)	125 W	140 W	145 W	195 W	250 W
	Power Consumption (Stand-by)	0.5 W	0.5 W	0.5 W	0.5 W	0.5 W
	Power Consumption (Typical)	52 W	63 W	68.9 W	81.9 W	94 W
Dimension	Display Dimensions (W x H x D)	963.9 x 558.9 x 59.6 mm / 37.9 x 22 x 2.3 in.	1,116.8 x 644.2 x 59.9 mm / 44 x 25.4 x 2.4 in.	1,230.5 x 707.2 x 59.9 mm / 48.4 x 27.8 x 2.4 in.	1,449.4 x 830.3 x 59.9 mm / 57 x32.7 x 2.4 in.	1,673.2 x 958.2 x 59.9 mm / 65.9 x 37.7 x 2.4 in.
	Package Dimension (W x H x D)	1,081 x 670 x 143 mm /	1,264 x 780 x 150 mm /	1,386 x 843 x 158 mm /	1,606 x 963 x 184 mm /	1,840 x 1,118 x 198 mm /
		42.6 x 26.4 x 5.6 in.	49.8 x 30.7 x 5.9 in.	54.6 x 33.2 x 6.2 in.	63.2 x 37.9 x 7.2 in.	72.4 x 44 x 7.8 in.
Weight	Display Weight	8.1 kg / 17.8 lbs.	11.4 kg / 25.1 lbs.	13.9 kg / 30.6 lbs.	20.6 kg / 45.4 lbs.	30.4 kg / 67 lbs.
	Package Weight Remote Controller Model	11.6 kg / 25.6 lbs. TM2140A	15.8 kg / 34.8. lbs. TM2140A	19.2 kg / 42.3 lbs. TM2140A	28.3 kg / 62.4 lbs. TM2140A	41.5 kg / 91.5 lbs. TM2140A
Accessory	Power Cable	Yes	Yes	Yes	Yes	Yes
	Quick Install Guide	Yes Yes	Yes	Yes	Yes	Yes
	Data Cable	Yes	Yes	Yes	Yes	Yes
	Data Cable	163	160	163	163	1 €3

Learn More samsung.com/display samsung.com/business insights.samsung.com

1-866-SAM4BIZ **Product Support**

Follow Us

youtube.com/samsungbizusa @SamsungBizUSA

SAMSUNG