



VPLFHZ57/W

4100lm WUXGA Laser
Projector, White.

\$7,000.00

U.S.List Price

Overview

The VPL-FHZ57 is Sony's next generation of the very successful Z-Phosphor projector illumination technology. With a brightness of 4100 lumens and 10,000 to 1 contrast ratio the VPL-Z57 offers high performance in demanding applications. The VPL-FHZ57 employs Sony's latest in image processing technology ensuring outstanding image quality. With Z-phosphor technology and a self-cleaning filter the VPL-FHZ57 offers peace of mind, need no maintenance for 20,000 hours. The VPI-FHZ57 comes with a powered zoom lens and with 4 other option lenses to cover a wide range of installation needs. The VPL-FHZ57 also has a large lens shift range ensuring installations go smoothly. The VPL-FHZ57 has a full set of input connections including HDMI, DVI and analog RGB with both an analog and digital monitor out. The VPI-FHZ57 also has a standard HDBaseT input for simple one cable connection

Highlights

* * Outstanding picture quality

4100 lumens 3LCD

Native WUXGA (1920 x 1200)

10000:1 Contrast Ratio

Ground-breaking laser light source

Up to 20,000h maintenance free design

Versatile inputs including HDMI and DVI-D

RJ45 for network control and

Up to V : +60% -0%, H : +/-32% Optical Lens Shift

Tilt angle free

Built-in Edge blending

Advanced Geometric Correction

Vertical and Horizontal Keystone correction : Max +/-30%

Equipped with Bright Era 3LCD Panels

12 bit 3D Digital Gamma

Near instantaneous power on

Auto light dimming for intelligently saving energy consumption

Designed to blend in visually

Picture by Picture Image Projection

DICOM GSDF Simulation Gamma Mode

Crestron RoomView Connected™

HG (Mercury) free

Full range of Option Lens"

Specifications

Optical Specifications		Detail
Image Device		3 LCD
Color Light Output		4100 lumens (light output mode : high), 3000 lumens (standard)
Light Output		4100 lumens (light output mode : high), 3000 lumens (standard)
Contrast Ratio		10,000:1
Projection Lens		Approx. 1.6x Powered zoom / Powered focus
Throw Ratio		1.39 to 2.31
Screen Coverage		60 to 600"
Input/Output Specifications		Detail
Analog RGB/Component In		15 Pin Hd
Digital In		HDMI and DVI
Network		RJ45 and HDBaseT
Monitor Out		DVI and 15 Pin HD
Remote Control		RS232C and IR
Electrical Specifications		Detail
Native Resolution		1920 by 1200
Video Resolution		NTSC3.58, PAL, SECAM, NTSC4.43, PAL-M, PAL-N, PAL60
Acceptable Computer Signals		Maximum display resolution : 1920 x 1200 dots
General Specifications		Detail
Dimensions (W x H x D)		18 1/8 x 6 3/5 x 20 3/8 in
Weight		16 kg
Power Requirements		100 - 240V
Power Consumption		308W
Fan Noise		32db

Accessories

Supplied Accessories		
Model:	Description:	U.S.List Price
	RM-PJ27 Remote Commander (1) Size AA battery (2) AC Power Cord (1) Cable ties (2) Quick Reference Manual (1) Operating Instructions (CD-ROM)	Pricing available upon request

	Warranty Card (1)	
Optional Accessories		
Model:	Description:	U.S.List Price
	PAM-600 ceiling mount VPLL-3003 Ultra Short Throw Lens 0.33:1 VPLL-3007 Short throw lens. 0.65:1 VPLL-Z3009 Short throw zoom lens 0.85- 1.0:1 VPLL-Z3024 Long throw zoom lens 2.34 - 3.19:1 VPLL-Z3032 Long throw zoom lens 3.18 - 4.84 :1	Pricing available upon request

Resources			
Product Manual			
Description:	Release Date	Type/Size	
VPLFHZ60-and-65-Operating-Instructions.pdf		pdf / 4,442K	Download now
Brochure			
Description:	Release Date	Type/Size	
FHZ576065-brochure.pdf		pdf / 2,267K	Download now