

## Image Display

|                        |                                       |
|------------------------|---------------------------------------|
| Display System         | 3-Chip 0.74" SXRD LCoS                |
| Native Chip Resolution | 4096 x 2160 (DCI 4K)                  |
| Supported Resolutions  | Maximum: DCI 4K - 4096 x 2160 @ 60 Hz |
|                        | White: 2500 Lumens                    |
|                        | Color: 2500 Lumens                    |
| Max Brightness         | Native: 1.85:1                        |
| Aspect Ratio           | Yes                                   |
| DLP Link 3D            | 12-Bit (68 Billion Colors)            |
| Color Depth            |                                       |

## Lens

|                 |                           |
|-----------------|---------------------------|
| Focus           | Manual Powered            |
|                 | Vertical: $\pm 6\%$       |
|                 | Horizontal: $\pm 3\%$     |
| Lens Shift      | Powered: 1.02x            |
| Optical Zoom    | 6 - 10" / 15.24 - 25.4 cm |
| Throw Distance  | 0.22:1                    |
| Throw Ratio     | 80 - 120" / 2.03 - 3.05 m |
| Projection Size |                           |

## Features

|                             |      |
|-----------------------------|------|
| Supported HDR Input Formats | Yes  |
| Ceiling Mountable           | Yes  |
| Rear Screen Projection      | Yes  |
| Built-In Speaker            | None |

## Input/Output Connectors

|                |                                               |
|----------------|-----------------------------------------------|
|                | 4 x HDMI (HDMI Type-A) Video Input            |
|                | 1 x RS-232 (DE-9/DB-9) Remote Input/Output    |
|                | 1 x 12 V Trigger Control Output               |
|                | 1 x 1/8" / 3.5 mm Mini Remote Input           |
|                | 1 x USB 2.0 (USB Type-A) Power Output         |
|                | 1 x Ethernet (RJ45) Control, LAN Input/Output |
| Inputs/Outputs | Version 2.2                                   |
| HDCP Support   |                                               |

## Hardware

|                      |      |
|----------------------|------|
| Wireless LAN / Wi-Fi | None |
|----------------------|------|

## General

|                     |                          |
|---------------------|--------------------------|
| Light Source        | Laser Phosphor           |
| Fan Noise           | Medium Brightness: 24 dB |
|                     | Arabic                   |
|                     | Dutch                    |
|                     | English                  |
|                     | French                   |
|                     | German                   |
|                     | Italian                  |
|                     | Japanese                 |
|                     | Korean                   |
| Supported Languages |                          |

|                        |                                               |
|------------------------|-----------------------------------------------|
|                        | Norwegian                                     |
|                        | Polish                                        |
|                        | Portuguese                                    |
|                        | Russian                                       |
|                        | Simplified Chinese                            |
|                        | Spanish                                       |
|                        | Swedish                                       |
|                        | Thai                                          |
|                        | Traditional Chinese                           |
|                        | Turkish                                       |
| AC Input Power         | 100 to 240 VAC, 50 / 60 Hz at 1.9 to 4.4 A    |
| Power Consumption      | Full Brightness: 436 W                        |
| Operating Temperature  | Standby Mode (Lamp Off): 0.5 W                |
| Storage Temperature    | 41 to 95°F / 5 to 35°C                        |
| Operating Humidity     | 14 to 140°F / -10 to 60°C                     |
| Storage Humidity       | 20 to 80%                                     |
| Dimensions (W x H x D) | 20 to 80%                                     |
| Weight                 | 36.4 x 8.6 x 19.4" / 925.0 x 218.5 x 493.8 mm |
| Packaging Info         | 77.16 lb / 35 kg                              |
| Package Weight         |                                               |
| Box Dimensions (LxWxH) | 96.15 lb                                      |
|                        | 39 x 22.4 x 17.5"                             |