

OF-170P-A1

17" PCAP Touch Monitor






Description

This industrial-grade, OF-170P-A1, 17" open frame monitor is the perfect solution for a wide variety of embedded applications. Uniquely designed with the glass settling proud of the bezel allowing for a seamless fit into a broad range of kiosks and fixtures, exceeding your integration expectations – The IP65 rating, 10-point touch, 1280 x 1024 resolution and innovative bezel design encourages a memorable end-user experience that outperforms the competition with a dependable, reliable, performance driven product.

Featured Specifications

- Size: 17" TFT LCD
- Maximum Resolution: 1280 x 1024
- Contrast Ratio: 800:1
- Aspect Ratio: 5:4
- Brightness: 250 nits (No Touch),
 215 nits (P-CAP)
- View Angle: H: 160°, V: 160°
- Video Port: 1 x VGA, 1 x DVI
- · Warranty: 3 year



Specifications

Touch Screen	Projected Capacitive
Touch Points	10
Touch Screen Interface	USB-HID (Type B)
I/O Ports	
Serial Port	_
USB Port	1 x USB 2.0 (Type B) for Touch Interface (USB-HID)
Video Port	1x VGA, 1x DVI
Audio Port	-
Remote Port	RJII
Power Input	1 x 2.1 mm 12V DC Jack
Physical Properties	
Power Supply	50W (12V, 4.16A) External Power Adaptor
Speaker	-
Housing Color	Dark Gray
Construction	Glass, SECC metal, Plastic (ABS)
Compliance	Front Panel IP65 Compliant, Rear IPX1
Dimensions (W x H x D) mm	394.0 x 330.0 x 57.1
Net Weight (kg)	4.8
Gross Weight (kg)	7.0
Carton (W x H x D) mm	480.0 x 415.0 x 160.0
VESA	75 x 75 mm, 100 x 100 mm
Ball Drop	-
Safety	
Certifications	CE/FCC
Environment	
Operating Temperature	0°C ~ 40°C, 20% ~ 80% RH. Non-Condensing
Storage Temperature	-20°C ~ 60°C, 10% ~ 90% RH. Non-Condensing
Optional Peripheral	
Remote Key	_

