

Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234

E-mail: saleshelp@tripplite.com

Model #: 3SP

3 Outlet, Commercial/Industrial-Grade Waber-by-Tripp Lite Power Strip



Highlights

- 3 outlets
- 6-ft. cord
- 8.6 in. overall length
- Lighted master power switch

Description

The Waber-by-Tripp Lite 3SP power strip offers a convenient method of power distribution in workbench, wallmount or floor mount applications. Includes 3 NEMA 5-15R output receptacles with 1.75-inch center-to-center spacing, 6-foot AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Corded, multi-outlet strip reduces cable clutter and permits connection of multiple electrical devices to a single AC wall socket. Unfiltered electrical pass-through makes the 3SP ideal for distributing alternate waveform UPS or generator power. Features a rugged all-metal housing, lighted power switch with transparent guard to prevent accidental shutoff, 15-amp resettable circuit breaker and attractive blue/gray color scheme. Lifetime warranty.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 3 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip

Applications

• Offers multiple outlet power distribution in workbench, wallmount or floor mount applications. Unfiltered electrical pass-through makes 3SP ideal for distributing alternate waveform UPS or generator power to protected equipment.

Package Includes

- 3SP Power Strip
- Warranty information
- Instruction manual

Features

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Includes 3 NEMA 5-15R output receptacles with 1.75-inch center-to-center outlet spacing
- Lighted power switch with transparent snap-over guard to prevent accidental shutoff
- Keyhole mounting tabs support permanent installation on a wide variety of surfaces
- UL1363 (USA), cUL (Canada)
- 15-amp power handling capacity with circuit breaker
- 6-foot AC line cord

Lifetime warranty

Specifications

OUTPUT				
Frequency compatibility	50 / 60 Hz			
Output volt amp capacity (amps)	15			
Outlet quantity / type	3 NEMA 5-15R			
Outlet spacing	1.75 in.			
Outlet orientation	Single row of 3			
INPUT				
Recommended Electrical Service	15A 120V			
Input connection type	NEMA 5-15P			
Input cord length (ft.)	6			
Input cord length (m)	1.8288			
Voltage compatibility (VAC)	120			
LEDS ALARMS & SWITCHES				
Switches	Illuminated 2 positon switch controls power to all outlets			
Locking switch cover	Transparent locking switch cover prevents accidental shutoff			
PHYSICAL				
Unit Dimensions (HWD/in)	7.38 x 2.5 x 1.5			
Unit Dimensions (HWD/cm)	18.7 x 6.35 x 3.8			
Material of construction	Metal			
Integrated keyhole mounting tabs	Keyhole mounting tabs enable mounting to a variety of surfaces			
Receptacle Color	Black			
AC line cord color	Black			
CERTIFICATIONS				
UL1363 (Power Tap)	UL1363			
cUL / CSA (Canada)	cUL			
WARRANTY				
Product Warranty Period (U.S., Canada & Puerto Rico)	Lifetime limited warranty			

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=1952.

improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.